

Material Safety Data Sheet

Page: 1 of 4

Infosafe No.	LPUK2	Issue Date : September 2005	ISSUED by PENRITEO
Product Name :	GEAR OIL EP 220, 460, 680		

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

Product Name	GEAR OIL EP 220, 460, 680
Product Code	GO220, GO460, GO680
Company Name	PENRITE OIL COMPANY P/L (ABN 005 001 525)
Address	88 Lewis Road Wantirna South Victoria 3152 Australia
Emergency Tel.	03 9801 0877 B.H
Telephone/Fax Number	Tel: 03 9801 0877
Recommended Use	Automotive/industrial gear oil.

2. HAZARDS IDENTIFICATION

Hazard Classification	NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. Hazard classification according to the criteria of NOHSC. Dangerous goods classification according to the Australia Dangerous Goods Code.
-----------------------	--

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Name	CAS	Proportion
	Long chain alkyl amine		0-1 %
	Ingredients determined not to be hazardous	Not required	Balance to 100%

4. FIRST AID MEASURES

Inhalation	If inhaled, remove from contaminated area. Apply artificial respiration if not breathing. If symptoms develop seek medical attention.
Ingestion	Do NOT induce vomiting. Wash out mouth with water. If symptoms develop seek medical attention.
Skin	Wash affected area thoroughly with soap and water. If symptoms develop seek medical attention.
Eye	If contact with the eye(s) occurs, wash with copious amounts of water holding eyelid(s) open. Take care not to rinse contaminated water into the non-affected eye. If symptoms persist seek medical attention.
First Aid Facilities	Eye wash and normal washroom facilities.
Advice to Doctor	Treat symptomatically.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media	CO2, Dry Chemical, Foam and Water Fog.
Hazards from Combustion Products	Normal combustion forms carbon dioxide and water. Incomplete combustion can produce carbon monoxide.
Specific Hazards	Combustible liquid. This product will burn if exposed to fire.
Hazchem Code	None Allocated
Precautions in connection with Fire	Fire-fighters should wear full protective clothing and self contained breathing apparatus (SCBA) operated in positive pressure mode.

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures	Wear appropriate personal protective equipment and clothing to minimise exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unnecessary personnel. If possible contain the spill. Place inert absorbent material onto spillage. Use clean non-sparking tools to collect the material and place into a suitable labelled container. Do not dilute material but contain. Dispose of waste according to federal, Environmental Protection Authority and state regulations. If the spillage enters the waterways contact the Environmental Protection Authority, or your local Waste Management Authority.
----------------------	--

Material Safety Data Sheet

Page: 2 of 4

Infosafe No.	LPUK2	Issue Date : September 2005	ISSUED by PENRITEO
Product Name :	GEAR OIL EP 220, 460, 680		

7. HANDLING AND STORAGE

Precautions for Safe Handling	Use in a well ventilated area. DO NOT store or use in confined spaces. Build up of mists or vapours in the atmosphere must be prevented. Avoid breathing in spray or mists or vapours. Do not use near welding or other ignition sources and avoid sparks. Do not smoke. When dealing with large quantities, repeated or prolonged skin exposure without protection should be prevented in order to lessen the possibility of skin disorders. It is essential that all who come into contact with this material maintain high standards of personal hygiene ie. washing hands prior to eating, drinking, smoking or using toilet facilities.
Conditions for Safe Storage	Store in a cool, dry well-ventilated area away from heat, sources of ignition, oxidising agents, foodstuffs, and clothing and out of direct sunlight. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Do NOT pressurise, cut, heat or weld containers as they may contain hazardous residues. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids. Reference should also be made to all State and Federal regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National Exposure Standards	No exposure standards have been established for this material, however, the TWA National Occupational Health And Safety Commission (NOHSC) exposure standards for oil mist is 5 mg/m ³ . As with all chemicals, exposure should be kept to the lowest possible levels.
Biological Limit Values	No biological limit allocated.
Engineering Controls	Provide sufficient ventilation to keep airborne levels below the exposure limit. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a local exhaust ventilation system is required. Refer to AS1940 - The storage and handling of flammable and combustible liquids and AS2430 - Explosive gas atmospheres for further information concerning ventilation requirements.
Respiratory Protection	If engineering controls are not effective in controlling airborne exposure then respiratory protective equipment should be used suitable for protecting against airborne contaminants. Final choice of appropriate breathing protection is dependant upon actual airborne concentrations and the type of breathing protection required will vary according to individual circumstances. Expert advice may be required to make this decision. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices.
Eye Protection	Safety glasses with side shields, goggles or full-face shield as appropriate recommended. Final choice of appropriate eye/face protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.
Hand Protection	Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.
Body Protection	Wear appropriate clothing including chemical resistant apron where clothing is likely to be contaminated. It is advisable that a local supplier of personal protective clothing is consulted regarding the choice of material.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Brown to black oil.
Odour	Not available.
Melting Point	Not available.
Boiling Point	Not available.
Solubility in Water	Negligible.

Material Safety Data Sheet

Page: 3 of 4

Infosafe No.	LPUK2	Issue Date : September 2005	ISSUED by PENRITEO
--------------	-------	-----------------------------	--------------------

Product Name : **GEAR OIL EP 220, 460, 680**

Specific Gravity	0.89 - 0.91 @ 15°C
pH Value	Not applicable.
Vapour Pressure	Not available.
Vapour Density (Air=1)	Not available.
Viscosity	19 - 31 cSt (100°C) 227 - 726 cSt (40°)
Flash Point	260°C
Auto-Ignition Temperature	Not available.
Flammable Limits - Lower	Not available.
Flammable Limits - Upper	Not available.

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under normal conditions.
Conditions to Avoid	Heat, direct sunlight, open flames or other sources of ignition.
Incompatible Materials	Not available.
Hazardous Decomposition Products	Thermal decomposition may result in the release of toxic and/or irritating fumes including carbon monoxide and carbon dioxide.
Hazardous Reactions	Hazardous polymerisation will not occur.

11. TOXICOLOGICAL INFORMATION

Inhalation	Inhalation of product vapours may cause irritation of the nose, throat and respiratory system.
Ingestion	Ingestion of this product may irritate the gastric tract causing nausea and vomiting.
Skin	May cause redness, itching and irritation.
Eye	May cause eye irritation, tearing, stinging, blurred vision, and redness.
Chronic Effects	Not available.

12. ECOLOGICAL INFORMATION

Ecotoxicity	No data is available for this material.
Persistence / Degradability	No data is available for this material.
Mobility	No data is available for this material.
Environ. Protection	Avoid contaminating waterways.

13. DISPOSAL CONSIDERATIONS

Disposal Considerations	Dispose of waste according to federal, EPA and state regulations.
-------------------------	---

14. TRANSPORT INFORMATION

Transport Information	Not classified as a Dangerous Good, according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.
U.N. Number	None Allocated
Proper Shipping Name	None Allocated
DG Class	None Allocated
Hazchem Code	None Allocated
Packing Group	None Allocated

15. REGULATORY INFORMATION

Material Safety Data Sheet

Page: 4 of 4

Infosafe No.	LPUK2	Issue Date : September 2005	ISSUED by PENRITOE
--------------	-------	-----------------------------	--------------------

Product Name : **GEAR OIL EP 220, 460, 680**

Poisons Schedule	Not Scheduled
1	2
3	4
5	6
7	8
9	10
11	12
13	14
15	16
17	18
19	20
21	22
23	24
25	26
27	28
29	30
31	32
33	34
35	36
37	38
39	40
41	42
43	44
45	46
47	48
49	50
51	52
53	54
55	56
57	58
59	60
61	62
63	64
65	66
67	68
69	70
71	72
73	74
75	76
77	78
79	80
81	82
83	84
85	86
87	88
89	90
91	92
93	94
95	96
97	98
99	100

16. OTHER INFORMATION

Date of preparation	MSDS created: June 2005.
or last revision of	MSDS reviewed: July 2005.

MSDS

Contact Person/Point TITLE: Technical and Marketing Director
TELEPHONE NUMBER: 03 9801 0877 B.H
...End Of MSDS...