

Material Safety Data Sheet

Page: 1 of 4

Infosafe No.	LPV48	Issue Date : February 2006	ISSUED by PENRITEO
Product Name :	HERITAGE ENGINE OIL LTM		

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name	HERITAGE ENGINE OIL LTM
Product Code	HERLTM
Company Name	PENRITE OIL COMPANY P/L (ABN 005 001 525)
Address	88 Lewis Road Wantirna South Victoria 3152 Australia
Emergency Tel.	03 9801 0877 B.H
Telephone/Fax Number	Tel: 03 9801 0877
Recommended Use	Engine oil for Vintage engines

2. HAZARDS IDENTIFICATION

Hazard Classification	NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. Hazard classification according to the criteria of NOHSC. Dangerous goods classification according to the Australia Dangerous Goods Code.
-----------------------	--

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Name	CAS	Proportion
	Ingredients determined not to be hazardous	Not required	60-100 %
	Zinc dialkyl dithiophosphate		0-2 %

4. FIRST AID MEASURES

Inhalation	If inhaled, remove from contaminated area. Apply artificial respiration if not breathing. If symptoms develop seek medical attention.
Ingestion	DO NOT INDUCE VOMITING. Wash out mouth with water. If symptoms develop seek medical attention.
Skin	Wash affected area thoroughly with soap and water. If symptoms develop seek medical attention.
Eye	If contact with the eye(s) occurs, wash with copious amounts of water holding eyelid(s) open. Take care not to rinse contaminated water into the non-affected eye. If symptoms persist seek medical attention.
First Aid Facilities	Eye wash and normal washroom facilities.
Advice to Doctor	Treat symptomatically.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media	Use foam, carbon dioxide or dry chemical.
Hazards from Combustion Products	Combustion produces oxides of carbon, nitrogen, zinc, phosphorous and sulphur.
Speical Protective Equipment for fire fighters	Fire-fighters should wear full protective clothing and self contained breathing apparatus (SCBA).
Specific Methods	Keep storage tanks, pipelines, fire exposed surfaces, etc. cool with water spray.
Specific Hazards	Water may cause splattering. Product will float on water.
Hazchem Code	None Allocated

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures	Slippery when spilt, avoid accidents. Wear appropriate personal protective equipment and clothing to minimise exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unnecessary personnel. If possible contain the spill. Place inert absorbent material onto spillage. Use clean non-sparking tools to collect the material and place into a suitable labelled container. Do not dilute material but
----------------------	---

Material Safety Data Sheet

Page: 2 of 4

Infosafe No.	LPV48	Issue Date : February 2006	ISSUED by PENRITEO
Product Name :	HERITAGE ENGINE OIL LTM		

contain. Dispose of waste according to federal, Environmental Protection Authority and state regulations. If the spillage enters the waterways contact the Environmental Protection Authority, or your local Waste Management Authority.

7. HANDLING AND STORAGE

Precautions for Safe Handling	Use in a well ventilated area. DO NOT store or use in confined spaces. Build up of mists or vapours in the atmosphere must be prevented. Avoid breathing in spray or mists or vapours. Do not use near welding or other ignition sources and avoid sparks. Do not smoke. It is essential that all who come into contact with this material maintain high standards of personal hygiene ie. washing hands prior to eating, drinking, smoking or using toilet facilities.
Conditions for Safe Storage	Store in a cool, dry well-ventilated area away from heat, sources of ignition, oxidising agents, foodstuffs, and clothing and out of direct sunlight. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Do NOT pressurise, cut, heat or weld containers as they may contain hazardous residues. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids. Reference should also be made to all State and Federal regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National Exposure Standards	No exposure standards have been established for this material, however, the TWA National Occupational Health And Safety Commission (NOHSC) exposure standards for oil mist is 5 mg/m ³ . As with all chemicals, exposure should be kept to the lowest possible levels.
Biological Limit Values	No biological limit allocated.
Engineering Controls	Provide sufficient ventilation to keep airborne levels below the exposure limit. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a local exhaust ventilation system is required. Refer to AS1940 - The storage and handling of flammable and combustible liquids and AS2430 - Explosive gas atmospheres for further information concerning ventilation requirements.
Respiratory Protection	If engineering controls are not effective in controlling airborne exposure then respiratory protective equipment should be used suitable for protecting against airborne contaminants. Final choice of appropriate breathing protection is dependant upon actual airborne concentrations and the type of breathing protection required will vary according to individual circumstances. Expert advice may be required to make this decision. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices.
Eye Protection	Safety glasses with side shields, goggles or full-face shield as appropriate recommended. Final choice of appropriate eye/face protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.
Hand Protection	Wear gloves of impervious material such as PVC or Nitrile gloves. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.
Body Protection	Wear appropriate clothing including chemical resistant apron where clothing is likely to be contaminated.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Yellow/brown liquid.
Odour	Not available.
Melting Point	Not available.
Boiling Point	Not available.

Material Safety Data Sheet

Page: 3 of 4

Infosafe No.	LPV48	Issue Date : February 2006	ISSUED by PENRITEO
--------------	-------	----------------------------	--------------------

Product Name : **HERITAGE ENGINE OIL LTM**

Solubility in Water	Insoluble
Specific Gravity	0.891 @ 15°C.
pH Value	Not available.
Vapour Pressure	Not available.
Vapour Density (Air=1)	Not available.
Viscosity	100 cSt @ 40°C 11.3 cSt @ 100°C
Flash Point	210°C.
Flammability	Combustible.
Auto-Ignition Temperature	Not applicable.
Flammable Limits - Lower	Not applicable.
Flammable Limits - Upper	Not applicable.

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under normal conditions.
Conditions to Avoid	Extremes of temperature and direct sunlight.
Incompatible Materials	Strong oxidising agents.
Hazardous Decomposition Products	Decomposition produces oxides of carbon, nitrogen, calcium, phosphorus, zinc and sulphur.
Hazardous Reactions	Reacts with strong oxidising agents.
Hazardous Polymerization	Will not occur.

11. TOXICOLOGICAL INFORMATION

Toxicology Information	No toxicology data available for this product.
Inhalation	Inhalation of product vapours may cause irritation of the nose, throat and respiratory system.
Ingestion	Ingestion of this product may irritate the gastric tract causing nausea and vomiting.
Skin	May cause redness, itching and irritation.
Eye	May cause eye irritation, tearing, stinging, blurred vision, and redness.

12. ECOLOGICAL INFORMATION

Ecotoxicity	No data available for this specific product.
Persistence / Degradability	Not available.
Mobility	Not available.
Environ. Protection	Avoid contaminating waterways.

13. DISPOSAL CONSIDERATIONS

Disposal Considerations	Dispose of waste according to federal, EPA and state regulations.
--------------------------------	---

14. TRANSPORT INFORMATION

Transport Information	Not classified as a Dangerous Good, according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.
U.N. Number	None Allocated
Proper Shipping Name	None Allocated

Material Safety Data Sheet

Page: 4 of 4

Infosafe No.	LPV48	Issue Date : February 2006	ISSUED by PENRITEO
--------------	-------	----------------------------	--------------------

Product Name : **HERITAGE ENGINE OIL LTM**

DG Class None Allocated

Hazchem Code None Allocated

Packing Group None Allocated

15. REGULATORY INFORMATION

Poisons Schedule Not Scheduled

16. OTHER INFORMATION

Date of preparation MSDS Reviewed: January 2006

or last revision of MSDS Supersedes: August 2000

MSDS

Contact Person/Point TITLE: Technical and Marketing Director
TELEPHONE NUMBER: 03 9801 0877 B.H
...End Of MSDS...