10 TENTHS PREMIUM 0

Package Sizes: 1 litre, 5 litre, 20 litre, 205 litre
Product Codes: FS0W50001, FS0W50005, FS0W50020, FS0W50205
Issue: November 2012

Description

The ultimate in extreme performance engine oils, 10 Tenths Premium Full Synthetic Engine Oils combine unique viscosity grades with cutting edge technology to deliver maximum engine protection in all conditions.

They use shear stable viscosity modifiers and a combination of synthetic PAO (Group 4) and ester (Group 5) base oils, contain full zinc levels and exceed the requirements of API SN/CF and JASO MA.

Application

Penrite 10 Tenths Premium 0 is an SAE 0W-50 oil specifically designed for use in high performance modern petrol engines in all types of vehicles, both on the road and on the track.

Penrite 10 Tenths Premium 0 is recommended for use where SAE 0W-40 oils are specified, including short-term high load competition, in extremes of both ambient and engine operating temperatures and where the manufacturer has specified the use of a fully synthetic engine oil. Ideal for use in engines sizes from 1 cylinder to 12 (or 16!) cylinders and also in motorcycles with wet clutches. May be used in European light duty petrol and diesel engines up to 2008 where ACEA A3/B4 is specified.

Note - Penrite 10 Tenths Premium Full Synthetic oils are only suitable for E85 fuel in competition and racing conditions only

Customer Benefits

- Recommended for naturally aspirated, supercharged and turbocharged engines.
- Suitable for use with avgas, methanol, nitro & E85 (racing & competition only) as well as conventional fuel.
- Longer engine life by reducing formation of high temperature engine deposits.
- Wear reduction from use of a combination of ultra-pure synthetic base oils and a European-standard additive package.
- Potentially longer oil life even in high performance vehicles.
- Reduced oil consumption due to use of highly specialised, ultra-pure, low volatility synthetic base oils.
- Non-friction modified so can be used in motorcycles with wet clutches.
- Very fast flow at start-up combined with full-bodied high temperature protection.
- Has Penrite's Extra 10 for extra protection at operating temperature.

Industry Specifications

API SN/CF	ACEA A3/B3	JASO MA	BMW LL-98
MB 229.1/229.3	VW 502.00/505.00	Porsche GL	

Typical Data

Viscosity, Kinematic, cSt	
at 40°C	108
at 100°C	18.7
Viscosity Index	194
Cold Cranking Viscosity, cP at -35°C	5770
Zinc, Mass %	0.125
Phosphorus, Mass %	0.113
Sulphated Ash, mass %	1.21
Base Number mg KOH/g	9.9

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
Victoria AUSTRALIA 3152, ABN 25 005 001 525
Enquiries: Phone 1300-PENRITE (1300 736 7483)
Fax: 1800-PENRITE (1800 736 7483)
International: Phone: 61 3 9801 0877,Fax: 61 3 9801 0977
New Zealand Ph: 0800 533 698, Fax: 0508 736 748
United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
Website: www.penriteoil.com, Email: penrite@penriteoil.com

PROUDLY AUSTRALIAN
FAMILY OWNED
SINCE 1926