LIMSLIP 90

Gearbox & Differential Oil

Issue: May 2016

PRODUCT CODE	PACK SIZE	CTN / QTY
LIM8090001	1 Litre	6

Product Description

Limslip 90 is a premium mineral automotive gear oil manufactured with modern extreme pressure additives and friction modifiers, meeting the requirements of API GL-5/6 and MT-1, as well as many other manufacturer specifications. It contains the correct dosage of **Limslip Additive** eliminating the need for a additional product when used in limited slip differentials. It is coloured **Blue** for easy identification.

Application

Limslip 90 is designed for use in differentials, both hypoid and limited slip, manual gearboxes, transfer cases and transaxles in passenger cars, light commercials, 4WDs, trucks, construction, earthmoving and agricultural equipment, where this viscosity grade is required.

Limslip 90 provides a superior level of protection in heavy duty conditions including shock loads, preventing wear and maintaining the life of critical parts. The multi-purpose formulation allows greater flexibility while minimising inventory levels, especially for differential applications

Limslip 90 can also be used in motorcycle drives, where such a grade is recommended and can also be used in 4-wheeler front differentials.

Product Benefits

- Maximum protection
- Anti-shudder additive technology
- Superior thermal stability
- Maintains cleanliness & reduces abrasive wear
- Longer drain intervals
- Superior protection against scoring & spalling wear
- Compatible with copper alloy components
- Minimises inventory

Industry Specifications

API GL-5/	API GL-6	API MT-1	API PG-2
Ford M2C1006-B	Ford M2C1013-A	Ford M2C104-A	Ford M2C105-A
FordM2C197-A	GM HN 1181	GM HN 1187	GM HN1386
GM HN1561	MIL-L-2105D	MIL-L-PRF-2105E	

Typical Data

Density at 15°C, kg/L	0.887
Viscosity, Kinematic, cSt	
at 40°C	131
at 100°C	14.3
Viscosity Index	131
Copper Corrosion Test	1b
Phosphorus, mass %	0.060

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.

ISO 9001:2008 REGISTERED FIRM

CERTIFICATE AU11/3876.00

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
Victoria AUSTRALIA 3152, ABN 25 005 001 525
Enquiries: Phone 1300-PENRITE (1300 736 748)
Fax: 1800-PENRITE (1800 736 748)
International: Phone: 61 3 9801 0877 Fax: 61 3 9801 0977
New Zealand Ph: 0800 533 698, Fax: 0508 736 748
United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
Website: www.penriteoil.com, Email: penrite@penriteoil.com

PROUDLY AUSTRALIAN
FAMILY OWNED
SINCE 1926