10 TENTHS RACING 20
20W-60

Codes: RACING20W60001, RACING20W60005, RACING2060020, RACING20W60205
Issue: August 2012

The ultimate in extreme performance, shear free, fully synthetic engine oil, Penrite 10 Tenths Racing 20 uses a combination of synthetic PAO and ester base oils and exceeds the requirements of API SN/CF and JASO MA.

Application

Penrite 10 Tenths Racing 20 is an SAE 20W-60, non friction-modified oil, recommended for use in short-term and long term high load competition, in extremes of both ambient and engine operating temperatures and where the manufacturer has specified the use of a fully synthetic engine oil. This grade is suitable for both road and track applications, including in four stroke motorcycles with wet clutches. It is suitable for "normal" on road use in a wide range of vehicles. May be used in light duty petrol and diesel engines up to 2008 where ACEA A3/B4 is specified.

Replaces SIN 20.

Customer Benefits

- Recommended for naturally aspirated, supercharged and turbocharged engines.
- Suitable for use with E85, avgas, methanol and nitro as well as conventional fuel.
- Longer engine life by reducing formation of high temperature engine deposits.
- Wear reduction from use of a combination of ultra-pure synthetic base oils and a European-standard additive package.
- Potentially longer oil life even in high performance vehicles.
- Shear free formulation reduces viscosity loss for maximum protection and maintenance of oil pressure *(fuel dilution may still occur and this can impact oil pressure).*
- Fast flow at start-up combined with full-bodied high temperature protection

Industry Specifications

API SN/CF	ACEA A3/B3	JASO MA	BMW LL-98	MB 229.1

Typical Data

Viscosity, Kinematic, cSt	
at 40°C	180
at 100°C	23.9
Viscosity Index	162
Cold Cranking Viscosity, cP at -15°C	6323
Zinc, Mass %	0.124
Phosphorus, Mass %	0.112
Sulphated Ash, mass %	1.20
Base Number	9.8

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect performance. A MSDS is available on request.

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
Victoria AUSTRALIA 3152, ABN 25 005 001 525
Enquiries: Phone 1300-PENRITE (1300 736 7483
Fax: 1800-PENRITE (1800 736 7483)
International: Phone: 61 3 9801 0877,Fax: 61 3 9801 0977
New Zealand Ph: 0800 533 698, Fax: 0508 736 748
United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
Website: www.penriteoil.com, Email: penrite@penriteoil.com

PROUDLY AUSTRALIAN
FAMILY OWNED
SINCE 1926