



# HPR Diesel 5 5W-40

## Semi Synthetic Engine Oil

Issue: June 2013

PENRITE

Product Code	Pack Size	Ctn / Qty
HPRD5001	1 Litre	6
HPRD5005	5 Litre	4
HPRD5010	10 Litre	1
HPRD5020	20 Litre	1
HPRD5060	60 Litre	1
HPRD5205	205 Litre	1
HPRD51000	1000 Litre	1



### Product Description

**HPR Diesel 5** is a premium high performance semi synthetic SAE 5W-40, non-friction modified engine oil. Contains a **DOUBLE LAYER** of engine wear protection with **FULL ZINC** and Penrite's advanced **EXTRA TEN** technology. It contains a combination of high technology additives, including increased dispersant levels and low shear viscosity modifiers. It Protects against corrosion, oil oxidation and sludge under all operating conditions.

**HPR Diesel 5** meets the requirements of API CI-4 PLUS/SL and ACEA A3/B4/E7 as well as many manufacturers' requirements

### Application

**HPR Diesel 5** is designed for use in modern 4, 6 & 8+ cylinder multi cam, multi valve (Including VVT), naturally aspirated, supercharged, turbocharged common rail & direct injection diesel engines. It is also suitable for diesel engines that are equipped hydraulically actuated injector units.

**HPR Diesel 5** features Penrite's Extra Ten technology that provides better wear protection, oil pressure and reduced oil consumption at operating temperature. It can be used where SAE 5W-30, SAE 5W-40, SAE 10W-30 & SAE10W-40 grade oils were originally recommended by the manufacturer.

**HPR Diesel 5** is suitable for use where fuel economy specifications ACEA A1/B1, A5/B5 and Global DLD-2 are specified in the owners handbook.

**HPR Diesel 5** is also suitable for use in petrol and LPG engines as a mixed fleet oil.

**HPR Diesel 5** is suitable for motorcycles with wet clutches

**HPR Diesel 5** is not suitable for vehicles fitted with a DPF (Diesel Particulate Filter)

### Vehicle Types

**HPR Diesel 5** is suitable for use in diesel engines in passenger cars, motorcycles, 4WD's, light & heavy duty commercial engines in trucks, tractors, agricultural & earthmoving equipment as well as industrial equipment such as fork lifts & stationary engines

### Fuel types

**HPR Diesel 5** is suitable for use with Diesel & Petrol/E10/LPG (Dual Fuel)

### Product Benefits

- **EXTRA TEN** technology offers the same engine wear protection at start up, but offers an extra layer of protection under all driving conditions compared to SAE 5W-30 engine oils.
- **FULL ZINC** anti-wear additive package for ultimate engine wear protection
- Low start-up viscosity allows easy starting in hydraulically actuated injector equipped engines
- Reduces oil consumption and maintains oil pressure
- Protects against corrosion, oil oxidation and engine sludge
- Reduces wear by controlling soot deposits



**PENRITE OIL COMPANY PTY LTD**, 88 Lewis Road, Wantirna South  
 Victoria AUSTRALIA 3152, ABN 25 005 001 525  
 Enquiries: Phone 1300-PENRITE (1300 736 748)  
 Fax: 1800-PENRITE (1800 736 748)  
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977  
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748  
 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234  
 Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN  
 FAMILY OWNED  
 SINCE 1926**





## Industry Specifications

API CI-4 PLUS/SL  
ACEA A3/B4/E7  
Global DLD-2/DLD-3  
JASO DH-1  
JASO MA

## Manufacturer Specifications

MB 228.3/229.3                      VW 502.00/505.00  
Ford M2C153-H/171-C/913-B/913-C

Opel B040 2098  
Peugeot PSA D-02

## Typical Data

Density at 15°C, kg/L	0.859
Viscosity, Kinematic, cSt	
at 40°C	100
at 100°C	14.7
Viscosity Index	152
Cold Cranking Viscosity, cP at -30°C	5,576
Zinc, Mass %	0.122
Phosphorus, Mass %	0.110
Sulphated Ash, mass %	1.34
Base Number	10.7

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.

# PENRITE



**PENRITE OIL COMPANY PTY LTD**, 88 Lewis Road, Wantirna South  
Victoria AUSTRALIA 3152, ABN 25 005 001 525  
Enquiries: Phone 1300-PENRITE (1300 736 748)  
Fax: 1800-PENRITE (1800 736 748)  
International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977  
New Zealand Ph: 0800 533 698, Fax: 0508 736 748  
United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234  
Website: [www.penriteoil.com](http://www.penriteoil.com), Email: [penrite@penriteoil.com](mailto:penrite@penriteoil.com)

**PROUDLY AUSTRALIAN  
FAMILY OWNED  
SINCE 1926**

