



10 Tenths Premium 0 0W-50

Premium PAO & Ester Synthetic Engine Oil

Issue: June 2013

Product Code	Pack Size	Ctn / Qty
FS0W50001	1 Litre	6
FS0W50005	5 Litre	4
FS0W50020	20 Litre	1
FS0W50205	205 Litre	1



Product Description

Premium 0 is a premium full synthetic PAO & Ester SAE 0W-50, non friction modified, modern engine oil. It contains a **DOUBLE LAYER** of engine wear protection with **FULL ZINC +** (exceeding 2200+ ppm levels) and Penrite's advanced **EXTRA TEN** technology.

Premium 0 exceeds the requirements of API SN/CF, ACEA A3/B3 and JASO MA as well as many manufacturers specifications.

Application

Premium 0 is for use in high performance modern engines for both on road and in competition applications. It is suitable for use in modern 4, 6 & 8+ cylinder, multi cam, multi-valve including VVT, naturally aspirated, supercharged & turbocharged engines, including light duty diesel engines.

Premium 0 is suitable for normal on road use in a wide range of vehicles. It can be used where SAE 0W-40 & SAE 5W-40 grade engine oils are specified. It may also be used in light duty petrol and diesel engines up to 2008 where ACEA A3/B4 is specified.

Premium 0 is suitable for use in four stroke motorcycles with wet clutches.

Vehicle Types

Premium 0 is suitable for use in passenger car, light commercial, competition vehicles and motor cycles.

Fuel types

Premium 0 can be used with Petrol, LPG, E10, E85 (Racing & Competition only), diesel (Without DPF), avgas, nitro, methanol & other conventional fuels.

Product Benefits

- Blended using **PAO** (Poly Alpha Olefin – Group IV) and **ESTER** (Group V) base oils for maximum heat resistance and high performance
- **FULL ZINC +** anti-wear additive package for ultimate engine wear protection
- **EXTRA TEN** which offers the same engine wear protection at start up but with an extra layer of protection under all driving conditions compared to 0W-40 & 5W-40 engine oils.
- **LATEST** oil specification technology exceeding petrol **API SN** for maximum wear protection, minimum sludge formation & reduced piston deposits
- Competition proven and trusted for performance engines
- Longer engine life by reducing formation of high temperature engine deposits
- Reduced oil consumption due to use of highly specialised, ultra-pure, low volatility synthetic base oils
- Non-friction modified so can be used in motorcycles with wet clutches
- Very fast flow at start-up combined with full-bodied high temperature protection

PENRITE



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
 Victoria AUSTRALIA 3152, ABN 25 005 001 525
 Enquiries: Phone 1300-PENRITE (1300 736 748)
 Fax: 1800-PENRITE (1800 736 748)
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748
 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
 Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
 FAMILY OWNED
 SINCE 1926**





Industry Specifications

API SN/CF
ACEA A3/B3
JASO MA

Manufacturer Specifications

BMW LL-98
MB 229.1 / 229.3
VW 502.00 / 505.00
Porsche GL

Typical Data

Viscosity, Kinematic, cSt	
at 40°C	108
at 100°C	18.7
Viscosity Index	194
Viscosity, Cold Cranking, cP @ -35°C	5770
CA content, mass %	0.299
P content, mass %	0.153
B content, mass %	0.064
Zn content, mass %	0.169
Sulphated Ash content, mass %	1.28
Base Number	9.9

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.

PENRITE



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
Victoria AUSTRALIA 3152, ABN 25 005 001 525
Enquiries: Phone 1300-PENRITE (1300 736 748)
Fax: 1800-PENRITE (1800 736 748)
International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
New Zealand Ph: 0800 533 698, Fax: 0508 736 748
United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
FAMILY OWNED
SINCE 1926**

