



# HPSO

## Full Synthetic Power Steering Fluid

Issue: July 2013



Product Code:	Pack Size:	Carton Qty:
HPSO001	1 Litre	6

### Product Description

**Penrite HPSO** is a premium fully synthetic oil specially designed for use in power steering and suspension units. It contains a unique combination of **anti-shudder** additives, dispersants and seal swell additives along with a specialised synthetic base oil to offer maximum wear protection, long service life and minimisation of viscosity loss.

### Application

**HPSO** is primarily designed and recommended for use in the power steering units of all Honda motor vehicles as well as Rover models 416i, 825 and 827 that use Honda power steering components.

**HPSO** may also be used in high performance applications in other vehicles such as Ford Tickford series, AU, BA & BF XR, FPV & Territory SX-SY series vehicles. The synthetic base oils and higher viscosity help to reduce pump wear and maintain steering feel where extra heat and load is expected in these applications.

**HPSO** is also suitable for use in motorcycle forks where a SAE Grade 20 oil is specified by the manufacturer.

*Penrite also market Power Steering Fluid, LHM Plus, PAS Fluid, MB 15, and LDAS special power steering and suspension fluids. Please check your handbook or call Penrite to clarify any applications for these products.*

### Customer Benefits

- Correct viscosity for Honda Power Steering units.
- Compatible with OEM fluid.
- Reduces power steering shudder (noise & chatter).
- Extends seal and hose life.
- Multiple use power steering & suspension
- Long Service life
- Protects against rust and corrosion.
- Reduces leakages.

### Industry Specifications

Honda PSF  
Honda PSF-V

Honda PSF-II  
Ford M2C-134D\*

Honda PSF-S

\* in performance models

### Typical Data

Colour	Straw
Density at 15°C, kg/L	0.871
Viscosity, Kinematic, cSt	
at 40°C	72
at 100°C	11.7
Viscosity Index	158
Zinc, mass %	0.139



Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. A MSDS is available on request.

**PENRITE OIL COMPANY PTY LTD**, 88 Lewis Road, Wantirna South  
Victoria AUSTRALIA 3152, ABN 25 005 001 525  
Enquiries: Phone 1300-PENRITE (1300 736 748)  
Fax: 1800-PENRITE (1800 736 748)  
International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977  
New Zealand Ph: 0800 533 698, Fax: 0508 736 748

**PROUDLY AUSTRALIAN  
FAMILY OWNED  
SINCE 1926**



**United Kingdom and EU** Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234  
Website: [www.penriteoil.com](http://www.penriteoil.com), Email: [penrite@penriteoil.com](mailto:penrite@penriteoil.com)