



HYPROID 85W-140

Gearbox & Differential Oil

Issue: May 2016

PRODUCT CODE	PACK SIZE	CTN / QTY
HYP85140001	1 Litre	6
HYP85140005	5 Litre	4
HYP85140020	20 Litre	1



PENRITE

Product Description

Hypoid 85W-140 is a premium, heavy duty, mineral automotive gear oil manufactured with extreme pressure additives meeting the requirements of API GL-5/6 and MT-1, as well as many other manufacturer specifications.

Application

Hypoid 85W-140 is designed for use in hypoid differentials in modern and classic passenger cars, light commercials, 4WD's as well as in on and off highway truck, construction and agricultural equipment where such a viscosity grade is required. For limited slip differentials, use **Penrite Limslip 85W-140**.

Hypoid 85W-140 can also be used in manual gearboxes and transfer cases, especially in some early models of trucks, where such an oil is recommended.

Hypoid 85W-140 provides a superior level of protection in heavy duty applications, where shock load conditions can be extreme. The additive technology provides maximum protection against wear and corrosion, maintaining the life of critical components.

Product Benefits

- Maximum protection, anti-shudder additive technology.
- Superior thermal stability.
- Maintains cleanliness and reduces abrasive wear of critical parts.
- Longer drain intervals by resisting high temperature degradation.
- Superior protection against scoring and spalling wear.

Industry Specifications

API GL-5
BTR 5M-36
Ford M2C1013-A
GM HN 1181
Mack GO-J
Rockwell O-76A

API MT-1
Clark MS-8
Ford ESW-M2C108-A
GM HN 1386
MIL-L-PRF-2105E
SAE J2360

API PG-2
Ford M2C105-A
Ford WSP-M2C197-A
International B-22
MIL-L-2105D
White MS-0016

Typical Data

Density at 15°C, kg/L	0.887
Viscosity, Kinematic, cSt	
at 40°C	131
at 100°C	14.3
Viscosity Index	131
Copper Corrosion Test	1b
Phosphorus, mass %	0.060



Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
Victoria AUSTRALIA 3152, ABN 25 005 001 525
Enquiries: Phone 1300-PENRITE (1300 736 748)
Fax: 1800-PENRITE (1800 736 748)
International: Phone: 61 3 9801 0877 Fax: 61 3 9801 0977
New Zealand Ph: 0800 533 698, Fax: 0508 736 748
United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
FAMILY OWNED
SINCE 1926**

