



MOTORCYCLE FORK 5 & 10 OILS

Package Size: 1 Litre

Product Codes: MCFO05001 / MCFO10001

Issue: May 2012

Motorcycle Fork 5 & Motorcycle Fork 10 Oils are fully synthetic, very high viscosity index fluids made from a special combination of synthetic base oils, viscosity modifiers and anti-wear and EP additives.

Application

Motorcycle Fork 5 & Motorcycle Fork 10 Oils are recommended for use in motorcycle forks and other suspension systems.

Motorcycle Fork 5 may be used in motorcycle forks that require SAE 5W and 7.5W grades. These include:

- Ducati
- KTM
- BMW
- Kawasaki
- Husqvarna
- Triumph

Motorcycle Fork 10 may be used in motorcycle forks that require SAE 10W and 15W grades. These include:

- Honda
- Moto Guzzi
- Kawasaki
- BMW
- Ducati
- Suzuki
- Yamaha

Note: If SAE 20W fork oils are required, Shocker Oil No 2 or HPSO is recommended.

Customer Benefits

- Stable viscosity over temperature variations
- Protects system from wear
- Compatible with brass and copper alloys
- Compatible with seal materials
- Excellent low temperature properties

Typical Data

Product	FORK 5	FORK 10
Density at 15°C, kg/L	0.847	0.856
Viscosity, Kinematic, cSt		
at 40°C	20	37
at 100°C	5.0	7.5
Viscosity Index	193	174
Zinc, mass %	0.139	0.139



Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
 Victoria AUSTRALIA 3152, ABN 25 005 001 525
 Enquiries: Phone 1300-PENRITE (1300 736 7483)
 Fax: 1800-PENRITE (1800 736 7483)
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748
 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
 Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
 FAMILY OWNED
 SINCE 1926**

