

# 10 Tenths Racing 10 10W-40

Premium 100% PAO & Ester Full Synthetic Engine Oil Issue: July 2014

Product Code	Pack Size	Ctn / Qty
RACING10W40001	1 Litre	6
RACING10W40005	5 Litre	4
RACING10W40020	20 Litre	1



## **Product Description**

**Racing 10** is a premium 100% PAO & Ester full synthetic SAE 10W-40, non friction modified, **SHEAR FREE** modern engine oil. It contains an anti wear package of **\*FULL ZINC +** (exceeding 2200+ ppm levels) for ultimate engine wear protection.

Racing 10 exceeds the requirements of API SN/CF, ACEA A3/B3 as well as many other manufacturers' specifications.

#### Application

**Racing 10** is for use in high performance modern petrol engines for both on road and in competition applications. It is suitable for use in modern 4, 6 & 8+ cylinder, multi-cam, multi-valve including VVT, naturally aspirated, supercharged and turbocharged engines.

**Racing 10** is a **Shear Free** formulation that eliminates viscosity loss and maintains oil pressure during extreme engine operating conditions ensuring the ultimate in protection for your engine.

**Racing 10** is suitable for "normal" on road applications in a wide range of vehicles. It can be used where SAE 10W-30 and SAE 10W-40 grade engine oils are specified. It may also be used in petrol and light duty diesel engines up to 2008 where ACEA A3/B4 is specified.

Racing 10 is suitable for use in four stroke motorcycles with wet clutches.

# Vehicle Types

**Racing 10** is suitable for use in competition applications and on road in passenger cars, motorcycles and light commercial vehicles.



SGS

### **Fuel types**

**Racing 10** can be used with Petrol, LPG, E10, E85 (Racing & Competition only), diesel (without DPF), avgas, nitro, methanol & other conventional fuels.

#### Product Benefits

- Blended using 100% PAO (Poly Alpha Olefin Group IV) and ESTER (Group V) full synthetic base oils for maximum heat resistance and high performance
- \*FULL ZINC + anti-wear additive package for ultimate engine wear protection
- SHEAR FREE formulation maintains oil pressure and eliminates viscosity loss
- LATEST oil specification technology exceeding petrol API SN for maximum wear protection, minimum sludge formation & reduced piston deposits
- COMPETITION PROVEN and trusted for performance engines
- Can be used in 4 stroke motor cycles with wet clutches.
- Longer engine life by reducing formation of high temperature engine deposits

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South Victoria AUSTRALIA 3152, ABN 25 005 001 525 Enquiries: Phone 1300-PENRITE (1300 736 748) Fax: 1800-PENRITE (1800 736 748) International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977 New Zealand Ph: 0800 533 698, Fax: 0508 736 748 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234 Website: www.penriteoil.com, Email: penrite@penriteoil.com

PROUDLY AUSTRALIAN FAMILY OWNED SINCE 1926



## **Industry Specifications**

API SN/CF ACEA A3/B3

#### **Manufacturer Specifications**

BMW LL-98 MB 229.1 / 229.3 VW 502.00 / 505.00 Porsche GL

# **Typical Data**

Viscosity, Kinematic, cSt	
at 40°C	92
at 100°C	14.6
Viscosity Index	167
Viscosity, Cold Cranking, cP @ -25°C	6105
Ca content, mass %	0.296
B content, mass %	0.063
Zn content, mass %	0.168
Base Number	9.8

\*Full Zinc + = Zinc level + Boron level combined as a total anti-wear package

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.





 PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South

 Victoria AUSTRALIA 3152, ABN 25 005 001 525

 Enquiries: Phone 1300-PENRITE (1300 736 748)

 Fax: 1800-PENRITE (1800 736 748)

 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977

 New Zealand Ph: 0800 533 698, Fax: 0508 736 748

 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234

 Website: www.penriteoil.com, Email: penrite@penriteoil.com

PROUDLY AUSTRALIAN FAMILY OWNED SINCE 1926