



Classic Mini 20W-50

Premium Mineral Engine Oil

Issue: May 2015

PRODUCT CODE	PACK SIZE	CTN / QTY
CLASMINI001	1 Litre (UK)	6
CLASMINI005	5 Litre	4



PENRITE

Product Description

Classic Mini is a premium mineral, full zinc, SAE 20W-50 viscosity, API SJ/CE, GL-4 engine oil, designed in conjunction with international Mini clubs and owners in the UK and Australia specifically for all classic Minis (Austin, BMC & Leyland). It has been designed to provide an excellent combination of engine protection and smooth gear shifts. It contains a full zinc anti-wear package (exceeding 1600+ PPM) for ultimate engine wear protection combined with premium quality base oils and additives that exceed original manufacturers specifications for these vehicles.

Application

Classic Mini has been developed for use in classic Mini's from 1959 to 2000 where a combined engine and gearbox utilises the same oil. It can also be used in other vehicles from the period including Mini Moke & Austin Metro. Classic Mini can be used in derivatives such as -

Austin 850	Austin Partner	Austin Mini	Austin Seven	Innocenti Mini
Leyland Mini	Mini Wildgoose	Morris 850	Morris Mascot	Morris Mini
Riley Elf	Rover Mini	Wolseley 1000	Wolseley Hornet	

Classic Mini is also suitable for other combined engine / gearbox vehicles manufactured by Austin, BMC & Leyland such as -

Morris 1000S, 1300 Nomad, 1100, 1100S, 1500, 1500 Nomad, 850 Van

Austin 1800 Mk 1 & MK 2, X6, Tasman / Kimberley (Aust)

Classic Mini has been formulated to replace older style 20W-40, 20W-50 or where straight 30 grades were originally used and specified.

Product Benefits

- Excellent combined engine and gearbox lubrication for all classic Minis
- Smoother gear shift and excellent gear wear protection
- SAE 20W-50, stay-in-grade engine protection
- Exceeds original manufacturers specifications
- Exceeds OEM's drain specifications
- Full zinc levels for wear protection
- Provides protection against rust & corrosion

Specifications

API SJ/CE, CCMC G2, API GL-4, MB 227.1, MIL-L-2104D

Typical Data

Density at 15°C, kg/L	0.879
Flash Point, °C	200
Viscosity, Kinematic, cSt	
at 40°C	176
at 100°C	20.0
Viscosity Index	131
Magnesium, mass %	Nil
Zinc, mass %	0.139
Phosphorus, mass %	0.142

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
 Victoria AUSTRALIA 3152, ABN 25 005 001 525
 Enquiries: Phone 1300-PENRITE (1300 736 748)
 Fax: 1800-PENRITE (1800 736 748)
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748
 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
 Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
 FAMILY OWNED
 SINCE 1926**

