



ENVIRO+ 10W-40

Full Synthetic Oil

Issue: May 2014

Product Code	Pack Size	Ctn / Qty
EPLUS10W40001	1 Litre	6
EPLUS10W40005	5 Litre	4
EPLUS10W40010	10 Litre	1
EPLUS10W40020	20 Litre	1
EPLUS10W40060	60 Litre	1
EPLUS10W40205	205 Litre	1



PENRITE

Description

Enviro+ 10W-40 is a highly advanced, full synthetic **OEM Warranty Approved**, extended drain/mixed fleet, ultra high performance diesel (UHPD) oil. It is formulated with the highest standard synthetic base oil and advanced additives to ensure protection against wear, corrosion, oil oxidation and sludge.

Enviro Plus 10W-40 is **Cummins CES 20081, Mack EO-O Premium Plus, Mercedes Benz 228.51, Renault RLD-3** and **Volvo VDS-4** manufacturer approved and meets API CJ-4/SM and ACEA E4/E6/E9 specifications.

Application

Enviro+ 10W-40 is primarily designed for use in modern four-stroke, low emission, naturally aspirated and turbocharged, light and heavy duty diesel engines including those with extended drain intervals of up to 100,000km in accordance with the OEM operating conditions.

Enviro+ 10W-40 meets the requirements of ACEA E4/E6/E9 and API CJ-4/SM and can be used where previous API specifications are recommended. It can be used where the manufacturer specifies either 10W-40 or 15W-40 oils of this and is also suitable for use in older engines requiring high performance ACEA E4/E6 oils such as Mercedes Benz Actros.

Enviro+ 10W-40 is suitable for use in the latest Euro IV and Euro V emissions European diesel engines including those that use SCR (Selective Catalytic Reduction) emissions systems along with those fitted with or without DPFs (Diesel Particulate Filters). Also suitable for use in normal or cooled EGR (Exhaust Gas Recirculation) systems, and 2001-on emissions engines where API CI-4 or higher oils are required. (Some of these engines also use **Penrite Penblue** as a part of their emission control systems).

Enviro+ 10W-40 is manufacturer approved by **Cummins, Mack, Mercedes Benz, Renault** and **Volvo**. It is also suitable for many Mercedes Benz Light Commercial and passenger car diesel engines where MB 228.31 or 228.51 are specified in the handbook. It can also be used in other light commercial and passenger cars if a full synthetic diesel engine oil is required or specified by the manufacturer.

Enviro+ 10W-40 is suitable for passenger car, 4WD's, light & heavy duty commercial vehicles, construction, mining and agricultural equipment. It can be used as a mixed fleet lubricant in both diesel and petrol driven vehicles. It is **NOT** recommended for use in motorcycles.

Product Benefits

- Maximises Diesel Particulate Filter life and engine performance
- Suitable for SCR and EGR systems
- Extended oil drains of up to 100,000km, reducing overall cost of ownership
- Controls oil consumption through use of low volatility, hydro-processed synthetic base oils
- Provides ideal wear, bore polish and deposit protection
- Effective dispersant additives keep soot in suspension, reducing wear
- Suitable for use in mixed fleets reducing inventory costs and misapplication
- Easier start up than 15W engine oils



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
 Victoria AUSTRALIA 3152, ABN 25 005 001 525
 Enquiries: Phone 1300-PENRITE (1300 736 7483)
 Fax: 1800-PENRITE (1800 736 7483)
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748
 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
 Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
 FAMILY OWNED
 SINCE 1926**





PENRITE

Industry Specifications

API CJ-4/SM

MB 228.31

DAF Extended Drain

ACEA E4/E6/E9

MAN 3277CRT/3477/3575

Caterpillar ECF-3-a

JASO DH-2

MTU Type 3

Approvals

MB-Approval 228.51

Volvo VDS-4

Cummins CES 20081

Mack EO-O Premium Plus

Renault RLD-3

Typical Data

Density at 15°C, kg/L

Viscosity, Kinematic, cSt

at 40°C

at 100°C

Viscosity Index

Viscosity, Cold Cranking, cP @ -25°C

Phosphorus, mass %

Zinc, mass %

Sulphated Ash, Mass %

Base Number

0.864

104

14.2

139

6,320

0.081

0.088

0.99

12.2

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
Victoria AUSTRALIA 3152, ABN 25 005 001 525
Enquiries: Phone 1300-PENRITE (1300 736 7483)
Fax: 1800-PENRITE (1800 736 7483)
International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
New Zealand Ph: 0800 533 698, Fax: 0508 736 748
United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
FAMILY OWNED
SINCE 1926**

