



Product Information

EXTREME PRESSURE GREASE

A NLGI No 2 general purpose grease manufactured from high quality base oils and a lithium soap.

APPLICATION

Extreme Pressure Grease is suitable for use in all general grease applications in automotive and industrial service.

This includes plain bearings, slow speed wheel and anti-friction bearings, chassis grease, general plant lubrication and agricultural and construction equipment lubrication.

CUSTOMER BENEFITS

- Protects against shock loadings.
- Resists water wash out.
- Protects against rust and corrosion
- Long service life.
- Tackiness additive helps grease stay in place.

INDUSTRY SPECIFICATIONS

NLGI 2

Typical Properties

Water Washout at 80°C, %	4
Base Oil Viscosity, ISO	220
Drop Point, °C	190
Colour	Brown
Timken OK Load, kg	18
Four Ball Weld Load, kg	250

Penrite Oil Company Pty Ltd
ABN 25 005 001 525
Ph: 1300 PENRITE (1300 736 748)
Int: 61 3 980 1 0877
Email: penrite@penriteoil.com
www.penriteoil.com.au

ENVIRONMENT, HEALTH AND SAFETY

Information is available by request on this product in the Penrite Material Safety Data Sheet. Information in this sheet is based on the most current information available. Minor variations to typical properties not affecting the performance of the product are to be expected in normal manufacture.

Issued September 2005