

GEAR BOX OIL 30 AND 40

Codes: GB30001, GB40001

Codes (UK Only): GB30001, GB30005, GB40001, GB40005

Issue: February 2012

Two multigrade gearbox oils meeting the requirements of API GL-1.

Many cars manufactured in the fifties and sixties specified engine oil (usually the same as that recommended in the engine) for use in the gearbox. Whilst it was convenient to offer this recommendation, no doubt a proper gear oil would have been a better alternative.

These two gear oils have been designed for this type of recommendation.

Application

Both oils can be used in vintage, veteran and classic gearboxes including those fitted with overdrives and those vehicles fitted with pre-selector gearboxes.

Gearbox 30 is an SAE 20W-60 oil designed for use where monograde 30 oils were originally specified.

Gearbox 40 is a 25W-70 oil designed for use where monograde 40 or 50 oils were originally specified.

Customer Benefits

- Do not contain friction modifiers so will not cause overdrives and pre-selector bands to slip.
- Do not contain EP additives so are compatible with synchro cones and other metal parts.

Typical Data

	GB30	GB40
Viscosity, Kinematic, cSt		
at 100°C	24.0	28.0





Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect

product performance. A MSDS is available on request. **PENRITE OIL COMPANY PTY LTD,** 88 Lewis Road, Wantirna South Victoria AUSTRALIA 3152, ABN 25 005 001 525

Enquiries: Phone 1300-PENRITE (1300 736 7483)

Fax: 1800-PENRITE (1800 736 7483)

International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977

New Zealand Ph: 0800 533 698, Fax: 0508 736 748

United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234

