



# HIGH TEMPERATURE WHEEL BEARING GREASE

Package Sizes: 450g cartridge, 500g, 2.5kg, 20kg, 55kg, 180kg

Product Codes: HTGR00045, HTGR0005, HTGR0025, HTGR020, HTGR055, HTGR180

Issue: June 2012

High Temperature Wheel Bearing Grease is an NLGI No 2, purple coloured, high temperature all-purpose, extreme pressure (EP) grease manufactured from high quality base oils and a lithium complex soap. It utilises a special borate additive system for effective extreme pressure performance and anti-wear protection.

## Application

High Temperature Wheel Bearing Grease is suitable for use in all general chassis grease applications in automotive and industrial service, including in cars, 4WDs, trucks and buses.

It is particularly suitable for use in wheel bearings of vehicles fitted with disc brakes, as well as drum brakes, boat trailer wheel bearings and other marine applications.

It is also a highly effective industrial grease in applications such as rolling element bearings, plain bearings, medium speed anti-friction bearings, steel mills, underground tunneling or mining and ore crushing plants, general plant lubrication and in agricultural and construction equipment.

## Customer Benefits

- Extreme pressure performance for protection against shock loadings
- Excellent resistance to water wash out
- Protects against rust and corrosion, even in salt water
- Long service life
- Lead and chlorine free
- Good pumpability
- Contains tackifiers to help grease stay in place

## Industry Specifications

NLGI 2	DIN 51502	ISO 6743	KP2N-30
ISO-L-XCDIB2	Volvo 97720 (level)		

## Typical Data

Appearance	Purple
Soap Type	Lithium Complex
NLGI Grade	2
Drop Point, °C	275
Base Oil Viscosity, ISO	220
Timken OK Load, kg	23
4-ball Weld Load, kg	620
Continuous Operating Temperature, °C	-10 to +170
Maximum Temperature, Intermittent use, °C	200



Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.

**PENRITE OIL COMPANY PTY LTD**, 88 Lewis Road, Wantirna South  
 Victoria AUSTRALIA 3152, ABN 25 005 001 525  
 Enquiries: Phone 1300-PENRITE (1300 736 7483)  
 Fax: 1800-PENRITE (1800 736 7483)  
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977  
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748  
 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234  
 Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN  
 FAMILY OWNED  
 SINCE 1926**

