



HPR

HPR 40

Premium Mineral 25W-70 Engine Oil

Issue: December 2015

Product Code	Pack Size	Ctn / Qty
HPR40001	1 Litre	6
HPR40005	5 Litre	4
HPR40020	20 Litre	1
HPR40060	60 Litre	1
HPR40205	205 Litre	1

Product Description

HPR 40 is a premium high performance mineral, 25W-70, non-friction modified engine oil. It contains a **DOUBLE LAYER** of engine wear protection with **FULL ZINC** (approx. 1500 ppm levels) and Penrite's advanced **EXTRA TEN** technology. Protects against corrosion, oil oxidation and sludge under all operating conditions.

Application

HPR 40 is designed for use in 4, 6 & 8+ cylinder naturally aspirated, supercharged and turbocharged petrol engines. It is particularly suited for use in larger capacity engines under high load conditions such as towing and competition or where ambient temperatures are high as well as where SAE 40 grade oil was originally recommended by the manufacturer.

HPR 40 features Penrite's Extra 10 in the oil's operating temperature that provides better wear protection, oil pressure and reduced oil consumption at operating temperature. It can be used where 25W-60 grade oils were originally recommended by the manufacturer. It also provides added protection for engines that are showing signs of excessive oil consumption and to maintain oil pressure.

HPR 40 is a high zinc formulation engine oil for greater protection of cam shafts, lifters and other internal engine parts from wear. No further zinc or other additive is needed with this product.

HPR 40 has been proven for years in race and competition conditions where it has an unequalled reputation for protection in engines requiring a high performance mineral oil. It is the product of choice for many competitors running competition vehicles in circuit & drag racing, rallying, drifting, hill climb, "targa" events, time trials and regularity.

Vehicle & Fuel Types

HPR 40 is suitable for use in passenger cars, competition vehicles, motorcycles & light commercial vehicles and is compatible with petrol & E10 for on road use & racing fuels such as Methanol, Nitro, Avgas, Alcohol & E85 for competition use. It is not recommended for diesel engines.

Product Benefits

- **EXTRA TEN** technology offers the same engine wear protection at start up, but offers an extra layer of protection under all driving conditions compared to SAE 25W-60 engine.
- **FULL ZINC** anti-wear additive package for ultimate engine wear protection
- Reduces oil consumption and maintains oil pressure
- Longer engine life by reducing formation of high temperature engine deposits
- Competition proven and trusted protection for racing engines



PENRITE



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
Victoria AUSTRALIA 3152, ABN 25 005 001 525
Enquiries: Phone 1300-PENRITE (1300 736 748)
Fax: 1800-PENRITE (1800 736 748)
International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
New Zealand Ph: 0800 533 698, Fax: 0508 736 748
United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
FAMILY OWNED
SINCE 1926**





Industry Specifications

API SL

Typical Data

Density at 15°C, kg/L	0.876
Viscosity, Kinematic, cSt	
at 40°C	290
at 100°C	28.6
Viscosity Index	133
Viscosity, Cold Cranking @ -10°C	6995
Zinc, mass %	0.145
Phosphorus, mass %	0.132
Sulphated Ash, mass %	0.85
Base Number	5.8

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.

PENRITE



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
Victoria AUSTRALIA 3152, ABN 25 005 001 525
Enquiries: Phone 1300-PENRITE (1300 736 748)
Fax: 1800-PENRITE (1800 736 748)
International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
New Zealand Ph: 0800 533 698, Fax: 0508 736 748
United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
FAMILY OWNED
SINCE 1926**

