



HPR DIESEL 20W-60

Package Sizes: 1 Litre, 5 Litre, 10 Litre, 20 Litre, 60 Litre, 205 Litre

Product Codes: HPRD001, HPRD005, HPRD010, HPRD020, HPRD060, HPRD205

Issue: August 2012

HPR Diesel is a premium mineral, SAE 20W-60, high viscosity diesel engine oil formulated to provide protection against wear, corrosion, oil oxidation and sludge under tough conditions. It meets the requirements of API CH-4/SJ and ACEA E7 as well as many manufacturers' requirements. It is also suitable for use where ACEA A3/B3 is specified in models prior to 2007.

Application

HPR Diesel is designed for use in turbocharged and naturally aspirated diesel engines in cars, light commercials and heavy duty engines in trucks, agricultural and earthmoving equipment. It is ideal for use in older engines or in high ambient conditions, or where the manufacturer has specified the use of SAE 30, SAE 20W-40 or 20W-50 grades. It can also be used in four stroke motorcycles with wet clutches.

May be used in older petrol and LPG engines as a mixed fleet oil.

Replaces Multi Truck 25

Customer Benefits

- Greater engine protection at operating temperatures compared to conventional diesel engine oils due to higher operating viscosity
- Longer engine life by reducing formation of high temperature engine deposits
- Reduces wear by controlling soot deposits
- Controls oil consumption due to high operating temperature viscosity

Industry Specifications

API CH-4/SJ	ACEA A3/B3/E7	VW 500.00	PSA D-99
Ford WSS-M2C911-A1	Renault RLD	Global DLD-1	MTU Type 2
MB 228.3	MAN 3275	Volvo VDS-2	JASO MA
JASO CD Plus			

Typical Data

Density at 15°C, kg/L	0.881
Viscosity, Kinematic, cSt	
at 40°C	227
at 100°C	24.5
Viscosity Index	136
Cold Cranking Viscosity, cP at -15°C	8,209
Zinc, Mass %	0.122
Phosphorus, Mass %	0.110
Sulphated Ash, mass %	1.22
Base Number	9.4



Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
 Victoria AUSTRALIA 3152, ABN 25 005 001 525
 Enquiries: Phone 1300-PENRITE (1300 736 748)
 Fax: 1800-PENRITE (1800 736 748)
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748
 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
 Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
 FAMILY OWNED
 SINCE 1926**

