



INDGREASE 100 LXEP2

Package Size: 450gm
Product Code: INDGR100LXEP200045
Issue: December 2012

Description

Indgrease 100 LXEP 2 is a premium, high melting point, lithium complex grease of NLGI 2 consistency. It is a high temperature grease designed to meet the most demanding grease applications especially where a low base oil viscosity and long life is required.

Indgrease 100 LXEP 2 is formulated to provide extreme pressure (EP) and anti-wear (AW) protection plus water resistance properties. Indgrease 100 LXEP 2 is also formulated to give a high level of oxidation, rust and corrosion protection.

Application

Indgrease 100 LXEP 2 is recommended for use in most types of industrial applications operating under high speed and conditions where shock loads, extreme pressure and vibration may occur. It can provide long life protection for rolling element bearings, plain bearings, gears and couplings in applications that include electric motors, pumps, fans & generators.

The recommended operating temperature range is from -20°C to 160°C. Indgrease 100 LXEP 2 grease can endure higher temperatures for short periods and/or if the lubrication frequency is increased.

Customer Benefits

- Reduced wear under high speed & shock loads
- Long life protection
- Superior protection against rust and corrosion
- High temperature capability
- Superior mechanical stability
- Excellent pumpability in centralised systems
- Excellent water resistance
- Outstanding storage stability
- Lead, Chlorine, Aromatic Extract and Nitrite free

Industry Specifications

NLGI 2	DIN 51502 KP2N-20	ISO 6743	ISO-L-XCDIB2
--------	-------------------	----------	--------------

Typical Data

Colour	Brown
Base Oil Viscosity, ISO	100
Drop Point, °C	275
Four Ball Weld Load, kg	315
Four Ball Wear Scar	0.55
Continuous Operating Temperature, °C	-20 to 160
Intermittent Use, °C	220



Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
 Victoria AUSTRALIA 3152, ABN 25 005 001 525
 Enquiries: Phone 1300-PENRITE (1300 736 748)
 Fax: 1800-PENRITE (1800 736 748)
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748
 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
 Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
 FAMILY OWNED
 SINCE 1926**

