



INDUS PRO HYDRAULIC OILS

Premium Mineral Oil

Issue: May 2015

| PRODUCT CODE | PACK SIZE | PRODUCT CODE | PACK SIZE |
|--------------|-----------|-----------------|------------|
| PROHYD10205 | 205 Litre | PROHYD46005 | 5 Litre |
| PROHYD22205 | 205 Litre | PROHYD46020 | 20 Litre |
| PROHYD32005 | 5 Litre | PROHYD46205 | 205 Litre |
| PROHYD32020 | 20 Litre | PROHYD461000LTR | 1000 Litre |
| PROHYD32205 | 205 Litre | HYD68001 | 1 Litre |
| PROHYD68005 | 5 Litre | PROHYD68020 | 20 Litre |
| PROHYD68205 | 205 Litre | PROHYD681000LTR | 1000 Litre |



PENRITE

Description

Indus Pro Hydraulic Oils are a premium mineral, high quality, low zinc, hydraulic oils made from selected base stocks and an advanced anti-wear additives. They are available in ISO 10, 22, 32, 46 & 68 grades to satisfy the requirements of stationary, mobile and industrial machines.

Application

Indus Pro Hydraulic Oils are recommended for use in all types of hydraulic systems using vane, piston or gear pumps, airline lubricators, vacuum pumps, lightly loaded gear sets and bearings (such as headstocks & windmill gears) as well as hydraulic hoists and jacks.

Indus Pro Hydraulic Oils can be used with silver components due to their low zinc content and are safe for all hydraulic hoses & seal types. They also provide outstanding protection against wear and corrosion.

Product Benefits

- Formulated to combat rust, oxidation, wear and foaming.
- Reduces sludge formation.
- Compatible with silver components.
- Provides good water separation.

Industry Specifications

Denison HF0, HF1, HF2
US Steel 126, 127

Vickers I-286-S, M-2950-S
Cincinnati Milacron P-68 (32), P-69 (68), P-70 (46) (HM)

DIN 51524 Part 2 (HLP Type)

Typical Data

| | PROHYD10 | PROHYD22 | PROHYD32 | PROHYD46 | PROHYD68 |
|-----------------------------------|----------|----------|----------|----------|----------|
| ISO Grade | 10 | 22 | 32 | 46 | 68 |
| Viscosity, Kinematic, cSt at 40°C | 11 | 19.2 | 30.2 | 44.6 | 72.1 |
| at 100°C | 2.8 | 4.3 | 5.1 | 6.7 | 9.0 |
| Viscosity Index | 116 | 131 | 94 | 103 | 98 |
| Zinc, mass % | NIL | NIL | 0.032 | 0.032 | 0.032 |

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
Victoria AUSTRALIA 3152, ABN 25 005 001 525
Enquiries: Phone 1300-PENRITE (1300 736 748)
Fax: 1800-PENRITE (1800 736 748)
International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
New Zealand Ph: 0800 533 698, Fax: 0508 736 748

**PROUDLY AUSTRALIAN
FAMILY OWNED
SINCE 1926**



United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
Website: www.penriteoil.com, Email: penrite@penriteoil.com