

MOTORCYCLE FORK OIL 5, 10 & 15

Suspension Fork Oils

Issue: October 2014

Product Code:	Pack Size:	Carton Qty:
MCFO05001	1 Litre	6
MCFO10001	1 Litre	6
MCFO15001	1 Litre	6



Description

Motorcycle Fork Oils 5, 10 and 15 are fully synthetic, very high viscosity index fluids made from a special combination of synthetic base oils, viscosity modifiers and anti-wear and EP additives.

Application

Motorcycle Fork Oils 5, 10 and 15 are recommended for use in motorcycle forks and other suspension systems.

Motorcycle Fork 5 may be used in motorcycle forks that require SAE 5W and 7.5W grades. These include:

- Ducati
- BMW
- Husqvarna

- KTM
- Kawasaki
- Triumph

Motorcycle Fork 10 may be used in motorcycle forks that require SAE 10W and 15W grades. These include:

- Honda
- Kawasaki
- Suzuki

- Moto Guzzi
- Ducati
- Yamaha

BMW

Motorcycle Fork 15 may be used in motorcycle forks that require SAE15W and 20W grades. These include:

- Aprilia
- Kawasaki
- Honda

- Moto Guzzi
- Suzuki
- Triumph

- VMoto
- Yamaha

Product Benefits

- Stable viscosity over temperature variations
- Protects system from wear
- · Compatible with brass and copper alloys
- Compatible with seal materials
- Excellent low temperature properties



Typical Data



Product		FORK 5	FORK 10	FORK 15
Density at 15°	C, kg/L	0.847	0.856	0.871
Viscosity, Kine	ematic, cSt			
	at 40°C	20	37	47
	at 100°C	5.0	7.5	8.9
Viscosity Inde	Х	193	174	173
Zinc, mass %		0.139	0.13	0.13

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South