



Penrite 4297

Gearbox Additive

Issue: June 2013

Product Code:	Pack Size:	Carton Qty:
PEN4297000150	150ml	12



Product Description

Penrite 4297 is a top-treat additive formulated to alleviate shift problems in automatic transmission systems and manual transmissions that utilise an automatic transmission fluid. Can also be used to reduce noise & wear in power steering systems of passenger vehicles.

Penrite 4297 contains a balanced mix of additives including oxidation inhibitors and friction modifiers to alter the shift feel of many transmissions while providing for an improved margin of protection in others.

Application

Penrite 4297 is formulated for use in the automatic transmissions of many cars to soften hard changes that may be occurring. It has been found to be particularly effective in the automatic transmissions of medium sized Japanese vehicles.

Penrite 4297 is designed for use in GM and Ford vehicles that are fitted with the BTR T-5, 5 speed manual gearbox and derivatives. Specific models include:

Ford 1991-1995 Falcon, XR6

Fairmont EB-EF Series

Holden 1993-1995 Commodore, Calais VR Series

Penrite 4297 can be used in heavy duty power steering systems such as Sheppard, to prevent metal to metal contact in the acme thread of the valve and shaft to reduce return and hard steer problems.

Penrite 4297 may also be used to alleviate baulking in manual transmissions that use auto transmission fluids.

Product Benefits

- Improves smoothness of gear change
- Compatible with current automatic transmission fluids
- Reduces noise and wear in power steering systems
- Reduces power steering squawk

Treat Rate:

Automatic Transmission Systems:

Passenger Cars: Add one bottle to the automatic transmission via the dipstick.

Power Steering Systems:

Passenger Cars: Add half of bottle to power steering reservoir.

Heavy Duty: Add one bottle to power steering reservoir per 2L of system capacity.

Typical Data

Colour	Dark Brown
Density at 15°C, kg/L	0.915
Phosphorus, mass %	0.110

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
 Victoria AUSTRALIA 3152, ABN 25 005 001 525
 Enquiries: Phone 1300-PENRITE (1300 736 748)
 Fax: 1800-PENRITE (1800 736 748)
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748
 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
 Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
 FAMILY OWNED
 SINCE 1926**



PENRITE

