



PRO ENGINE OILS

5, 10 and 20

Codes: **PRO05020, PRO05205, PRO10020, PRO10205, PRO20020, PRO20205**

Issue: October 2011

A range of cost effective, multigrade oils, designed for use by workshops and garages for petrol engines and light duty diesel engines. Pro Engine Oils are blended with the latest technology additives along with 100% pure hydrocracked base stocks.

APPLICATION

Pro 5 is recommended where the manufacturer requires a 7.5W-30 or 5W-30 engine oil and meets the MY2010 US requirements for catalyst compatibility.

Pro 10 is recommended where the manufacturer requires a 7.5W-30 or 10W-30 engine oil and meets the MY2010 US catalyst compatibility requirements. Ideal for the Ford AU/BF/FG Series and Holden VT-II/VX/VY/VZ/VE Series.

Pro 20 is ideal for use in most older engines and is a good general workshop grade.

Although Pro Engine Oils may be used in gas and some older diesel engined cars, 4WDs and light commercials our primary recommendations are the appropriate HPR Gas and HPR Diesel products or Penrite Diesel FX or Diesel HD.

** European made vehicles requiring these types of viscosity grades should use the appropriate HPR engine oil. Pro 5 and Pro 10 are not designed for vehicles that require ACEA C1, C2, C3 or C4 oils. Use the appropriate Penrite Enviro Plus oil in those applications.*

Customer Benefits

- Catalytic converter compatible.
- Cost effective products meeting warranty requirements for new vehicles.

Industry Specifications

Pro 5	API SN Resource Conserving, ILSAC GF-5
Pro 10	API SN Resource Conserving, ILSAC GF-5
Pro 20	API SM/CF

Also available is Pro Extra and Pro 15 Plus

Typical Data

	PRO 5	PRO 10	PRO 20
SAE Grade	5W-30	10W-30	20W-50
Density at 15°C, kg/L	0.851	0.866	0.877
Viscosity, Kinematic, cSt			
at 40°C	63	60	157
at 100°C	11.0	9.8	19.3
Viscosity Index	169	148	140
Viscosity, Cold Cranking @ -15 °C			6,680
Viscosity, Cold Cranking @ -25 °C		3,966	
Viscosity, Cold Cranking @ -30 °C	5,020		
Zinc, mass %	0.085	0.082	0.110
Sulphated Ash, mass %	0.93	0.95	1.08
Base Number	7.2	8.3	8.2



Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. A MSDS is available on request.

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South Victoria AUSTRALIA 3152, ABN 25 005 001 525

Enquiries: Phone 1300-PENRITE (1300 736 7483)

Fax: 1800-PENRITE (1800 736 7483)

International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977

New Zealand Ph: 0800 533 698, Fax: 0508 736 748

United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234

Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
FAMILY OWNED
SINCE 1926**

