



# PRO GEAR 80W-140

## Full Synthetic Gear Oil

Issue: June 2014

Product Code	Pack Size	Ctn / Qty
PROG80140001	1 Litre	6
PROG801400025	2.5 Litre	4
PROG80140020	20 Litre	1
PROG80140060	60 Litre	1
PROG80140205	205 Litre	1



### Description

**Pro Gear 80W-140** is a premium full synthetic, SAE 80W-140, heavy duty gear oil that uses a special combination of synthetic base oils which include PAO and Ester, with an advanced additive system to provide ultimate performance and protection under all operating conditions. It meets the performance requirements of API GL-5/GL-6/MT-1 as well as many other manufacturers specifications.

### Application

**Pro Gear 80W-140** is designed for use in manual gearboxes, transaxles and differentials of competition vehicles, passenger cars, 4WDs, light & heavy duty commercials, trucks, buses, agricultural and earthmoving equipment.

**Pro Gear 80W-140** can be used in applications requiring a SAE 85W-140, 75W-140 or SAE 140 gear oil or where a synthetic oil of this viscosity is required especially where consistent high temperature operations and/or extreme loads are encountered.

**Pro Gear 80W-140** is already dosed with the correct amount of friction additive for use in limited slip differentials, no extra additive is required, nor should it be added as seal degradation may result.

**Pro Gear 80W-140** can be used as a replacement for a mineral gear oil, of a similar viscosity, operating in severe applications, such as high temperatures and shock loads that may lead to a mineral oil breaking down prematurely. Its resistance to high temperature degradation and oxidation allows it to provide longer oil drain intervals while providing maximum wear protection.

**Pro Gear 80W-140** has been especially formulated (and field trial-proven) to reduce chatter and whine in BTR/Dana M78/M80 limited slip differentials fitted to V8 Holdens and Fords as well Chrysler & Jeep vehicles.

### Product Benefits

- Ultimate protection, race proven performance.
- Longer drain intervals due to extreme heat resistance.
- Superior protection against scoring & spalling wear caused by repeated shock load conditions.
- Compatible with copper alloy components and protects against corrosion.
- Minimises chatter in high performance competition and on-highway limited slip differentials.
- Minimises inventory as separate limited slip products are not required.

### Industry Specifications

API GL-5/API GL-6/MT-1	MIL-L-PRF-2105E	Ford M2C190-A	GM HN 2040
BTR/Dana	Mack GO-J	Eaton Axle Bulletin 90-104	
ZF TE-ML05B/07A	SAE J2360	Rockwell O-76-B	

### Typical Data

Density@ 15 °C	0.894
Viscosity, Kinematic, cSt	
at 40°C	263
at 100°C	30.5
Viscosity Index	157
Pour Point, °C	-30.0
Viscosity, Brookfield, cP @ -26 °C	58,900
Phosphorus, mass %	0.236

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.



**PENRITE OIL COMPANY PTY LTD**, 88 Lewis Road, Wantirna South  
 Victoria AUSTRALIA 3152, ABN 25 005 001 525  
 Enquiries: Phone 1300-PENRITE (1300 736 748)  
 Fax: 1800-PENRITE (1800 736 748)  
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977  
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748  
 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234  
 Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN  
 FAMILY OWNED  
 SINCE 1926**

