



RADIATOR INHIBITOR

Codes: RI020

Issue: August 2012

A low silicate and phosphate based, cost-effective, water based inhibitor concentrate.

APPLICATION

Cooling systems of automotive engines where anti-freeze and/or anti-boil properties are not required.

Use at a ratio of 50ml per litre of cooling system capacity, ie 1 part inhibitor plus 19 parts water.

Please note this product is NOT an anti-freeze. If travelling to snow areas, please use one of the Penrite 3YR, 4YR or 5YR Anti Freeze Anti Boil products.

Customer Benefits

- 2 years/40,000km drain intervals if used and maintained correctly.
- Protects all internal surfaces from corrosion, including aluminium.
- Contains an anti foam agent to help protect against cavitation erosion.
- Cost effective engine protection

Industry Specifications

AS 2108-2004 Type B, ESR FM7C 35C, R1-4C

Typical Data

Density at 15°C, kg/L
Colour

1.08
Green

PENRITE



Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect performance. A MSDS is available on request.

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
Victoria AUSTRALIA 3152, ABN 25 005 001 525

Enquiries: Phone 1300-PENRITE (1300 736 7483)

Fax: 1800-PENRITE (1800 736 7483)

International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977

New Zealand Ph: 0800 533 698, Fax: 0508 736 748

United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234

Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
FAMILY OWNED
SINCE 1926**

