



VALVESHIELD

Valve Saver & Upper Cylinder Fluid

Issue: April 2015

Product Code	Pack Size	Ctn / Qty
ADVS250	250ml	6
ADVS001	1 Litre	6



PENRITE

Product Description

Valveshield is a dual purpose fuel additive treatment formulated for vehicles that were originally designed to run on leaded fuel and vehicles that run on LPG, CNG, Petrol & Petrol/LPG (dual fuel systems). It protects engines manufactured to run on leaded fuel and LPG against valve seat recession (VSR) whilst protecting them from intake deposit build up.

Application

Valveshield is designed for use in all engines in passenger cars, 4WDs, light commercial vehicles, motorcycles and stationary engines that were designed to run on leaded petrol or LPG including vehicles fitted with LPG dripper systems.

Valveshield acts as a lead replacement additive in unleaded petrol protecting the engine from VSR in those that have not had hardened valves and seats installed post original manufacture.

Valveshield will assist in keeping the fuel system clean and protect the system components for better engine performance and fuel economy and is safe for use in vehicles fitted with catalytic converters and oxygen sensors. It can be used with Petrol, LPG & CNG. It is NOT SUITABLE for use with Ethanol fuel blends (E10/E85)

For best results:

- Add **Valveshield** prior to filling fuel tank
- 50 ml treats 50 litres of unleaded petrol for prevention of VSR and upper cylinder lubrication
- For added cleaning benefits use 100 ml per 50 litres of petrol
- Use at each fuel fill if protecting a vehicle designed to run on leaded petrol from VSR

Product Benefits

- Protects against Valve Seat Recession
- Cleans and protects fuel system components
- Provides a lubricant into the fuel system which is absent with the "dry" LPG
- Prevents power loss by lowering intake deposits on valves
- Will not harm catalytic converters or oxygen sensors
- Maintains optimum compression by preventing cylinder head damage
- Extends the life of fuel pumps and injection systems
- Protects against rust corrosion and wear
- Suitable for late model vehicles

Typical Data

Colour	Red
Viscosity cSt @ 100°C	11.4
Viscosity cSt @ 40°C	75
Density at 15°C	0.873 g/ml
Flashpoint °C	76°C

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect performance. A MSDS is available on request.



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
 Victoria AUSTRALIA 3152, ABN 25 005 001 525
 Enquiries: Phone 1300-PENRITE (1300 736 748)
 Fax: 1800-PENRITE (1800 736 748)
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748

**PROUDLY AUSTRALIAN
 FAMILY OWNED
 SINCE 1926**



United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
 Website: www.penriteoil.com, Email: penrite@penriteoil.com