

# **ENDURO**

#### **Premium Mineral Oil**

Issue: March 2014

Product Code	Pack Size	Ctn / Qty	
END005	5 Litre	4	
END020	20 Litre	1	
END205	205 Litre	1	



### **Description**

**Enduro** is a non friction modified, high zinc, 25W-70 four-stroke motorcycle engine oil that offers outstanding protection for older and classic motorcycles that required a SAE 40 grade engine oil.

### **Application**

**Enduro** is primarily recommended for use where SAE 40 oils were specified and is ideal for use in pre 1992 **Evolution** engined **Harley Davidson** and large capacity (greater than 600cc) European motor cycles in severe service operation such as in competition and in high ambient temperatures. It is also ideal for those motorcycles with high mileages that are burning lighter viscosity grade oils.

**Enduro** may also be used in older large capacity Japanese bikes in competition and in Classic British & European motorcycles including single cylinder 350 to 500cc low revving engines and 500 to 650cc parallel twins. It is ideal for classic –

H M R	rial arley Davidson otobecane abbit	BMW Heinkel Moto-Guzzi Royal Enfield	BSA Indian Norton Sunbeam	Douglas ISO NSU Triumph	Ducati JAWA Panther Velocette	Gilera Matchless Parilla Victoria
V	incent					

### **Product Benefits**

- Maintains oil pressure and reduces oil consumption.
- Full Zinc additive package for outstanding wear protection
- · Maintains engine cleanliness.
- Non-friction modified to maintain clutch effectiveness.
- · Selected blend of viscosity modifiers maintains the oil film even in combined engine/gear box units.

## **Industry Specifications**

API SG

### **Typical Data**

Density at 15°C, kg/L	0.890
Flash Point, °C	238
Viscosity, Kinematic, cSt	
at 40°C	269
at 100°C	28.1
CCS Viscosity @ -10°C, cP	6379
Viscosity Index	138
Zinc, mass %	0.176
Phosphorus, mass %	0.160
Sulphated Ash, mass %	0.98
Mo content, % mass	0.004
Base Number	7.4





Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South Victoria AUSTRALIA 3152, ABN 25 005 001 525 Enquiries: Phone 1300-PENRITE (1300 736 748)

Fax: 1800-PENRITE (1800 736 748)
International: Phone: 61 3 9801 0877,Fax: 61 3 9801 0977

New Zealand Ph: 0800 533 698, Fax: 0508 736 748

PROUDLY AUSTRALIAN FAMILY OWNED SINCE 1926