



EVERYDAY DRIVING 5W-30, 10W-30, 15W-40 and 20W-50 STOPS OILS BURNING 30-70

Codes: *PMO05005, PMO10005, PMO15005, PMO20005, PMO30005*

Issue: October 2011

Penrite Engine Oils, Everyday Driving 5W-30, 10W-30, 15W-40 and 20W-50 and Stops Oil Burning 30-70 are cost effective high quality mineral engine oils for use in a wide range of vehicles.

Application

Penrite Everyday driving 5W-30 is suitable for all non-European vehicles that require SAE 5W-30 mineral oils meeting ILSAC GF-3 and API SL. As a full mineral product, it is our prime recommendation for use in the Mazda RX-8 Renesis Rotary engine.

Penrite 10W-30, 15W-40 and 20W-50 are suitable for everyday driving conditions and may be used in petrol, diesel or gas engines where these viscosity grades are specified. Not recommended for modern European engines.

Penrite 30-70 Stops Oil Burning is designed for old car petrol engines where there is excessive oil consumption due to worn rings or bores.

Although these oils are described as cost effective they still are able to provide:

- Protection of engine parts
- Resistance to oil thickening
- Catalyst compatibility
- Good oil life
- Maintenance of oil pressure

Typical Data

Product	5W-30	10W-30	15W-40
Performance	SL/CF/MA/GF-3	SL/CF/MA/GF-3	SL/CF-4/MA
Density at 15°C, kg/L	0.865	0.865	0.879
Viscosity, Kinematic, cSt			
at 40°C	64	68	115
at 100°C	11.0	10.6	15.1
Viscosity Index	165	144	123
Viscosity, Cold Cranking @ -30 °C	6,209		
Viscosity, Cold Cranking @ -25 °C		4,371	
Viscosity, Cold Cranking @ -20 °C			6,065
Zinc, mass %	0.108	0.108	0.108
Sulphated Ash, mass %	0.83	0.83	0.83
Base Number	7.6	7.6	7.6
Product	20W-50	30-70	
Performance	SL/CF-4/MA	SJ	
Density at 15°C, kg/L	0.879	0.879	
Viscosity, Kinematic, cSt			
at 40°C	169	271	
at 100°C	18.5	29.3	
Viscosity Index	148	145	
Viscosity, Cold Cranking @ -15 °C	8,503		
Zinc, mass %	0.108	0.110	
Sulphated Ash, mass %	0.83	0.88	
Base Number	7.6	5.8	



Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. A MSDS is available on request.

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
Victoria AUSTRALIA 3152, ABN 25 005 001 525

Enquiries: Phone 1300-PENRITE (1300 736 7483)

Fax: 1800-PENRITE (1800 736 7483)

International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977

New Zealand Ph: 0800 533 698, Fax: 0508 736 748

United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234

Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
FAMILY OWNED
SINCE 1926**

