



GRAPHITE GREASE

Codes: GRGR0005
Issue: October 2011

A graphite impregnated calcium grease meeting NLGI 3.

Application

Designed for the lubrication of spring leaves, handbrake cables, flexible drives and exposed chains.

Should not be used in wheel bearings or where temperatures are likely to exceed 60°C.

Can also be used in slow speed plain bearings and slides where a heavy grease with solid lubricants is required. It can also be used in industrial and construction equipment including bulldozers, scrapers, loading shovels and dump trucks where a graphited grease is recommended and high temperature capability is not required. It can be used in plain bearing locks, latches and fasteners, cables and springs and even as a fifth wheel lubricant.

Customer Benefits

- Good resistance to water washout
- Long service life
- Protects against wear, rust and corrosion

Industry Specifications

NLGI 3

Typical Data

Appearance	Grey/Black
Soap Type	Calcium
NLGI Grade	3
Drop Point, °C	80
Graphite Content, %	15

PENRITE



Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. A MSDS is available on request.

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
Victoria AUSTRALIA 3152, ABN 25 005 001 525

Enquiries: Phone 1300-PENRITE (1300 736 7483)

Fax: 1800-PENRITE (1800 736 7483)

International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977

New Zealand Ph: 0800 533 698, Fax: 0508 736 748

United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234

Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
FAMILY OWNED
SINCE 1926**

