



HD OIL

Premium Mineral Oil

Issue: February 2014

Product Code	Pack Size	Ctn / Qty
HD005	5 Litre	4



PENRITE

Description

HD Oil is a premium, heavy duty, high performance mineral, SAE 25W-70, non friction modified, 4 stroke engine oil. It contains a superior anti wear and cleansing package package of **FULL ZINC** (exceeding 1750+ ppm levels) for ultimate engine, gearbox & clutch protection and special detergents and dispersants for protection in the harshest of on and off road conditions for older and classic motorcycles.

Application

HD Oil is primarily recommended for use in classic motorcycles where **SAE 50 & SAE 60** monograde oils were specified. It is also equally suitable for use in transmissions with wet clutch systems where engine & gearbox oils are combined. It has optimum clutch slip prevention in these systems.

HD Oil is particularly suited to be used in pre-Evolution (1984) engined **Harley Davidson** motor cycles. Specific models such as –

- 1000 cc / 1200 cc Panheads (1948 – 1965)
- 1200 cc / 1340 cc Shovelheads (1966 -1985)
- 1200 cc Electraglides (1978 - 1985)
- 1000 cc Sportsters & Roadsters (1978-1985)
- All side valve models to (1903 -1969)

HD Oil is also suitable for other large V-Twin bikes such as **Ducati, Hummel, Indian, NSU, PUCH, Henderson & early Buell.** HD Oil is also ideal oil for Classic British motorcycles such as **Norton, AJS & BSA** including single cylinder 350 to 500cc low revving engines and 500 to 650 cc Parallel twins.

Product Benefits

- **FULL ZINC** anti-wear additive package for ultimate engine wear protection
- **MAXIMUM** power and acceleration
- **FACTORY PROVEN** by competition race teams and trusted protection for performance engines
- **MAINTAINS** oil pressure and controls oil consumption
- **OPTIMUM** clutch slip prevention in 4 stroke motor cycles with wet clutches.
- Extends engine life by reducing formation of high temperature engine deposits

Industry Specifications

API SF

Typical Data

Density at 15°C, kg/L	0.890
Viscosity, Kinematic, cSt	
at 40°C	281
at 100°C	28.8
Viscosity Index	137
CCS Viscosity @ -10°C, cP	5336
Flash Point °C	238
Sulphated Ash, mass %	0.98
Zinc, mass %	0.176
Phosphorus, mass %	0.160
Ca content, mass%	0.207
Mo content, mass %	0.004
Base Number	7.4



Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
 Victoria AUSTRALIA 3152, ABN 25 005 001 525
 Enquiries: Phone 1300-PENRITE (1300 736 748)
 Fax: 1800-PENRITE (1800 736 748)
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748

**PROUDLY AUSTRALIAN
 FAMILY OWNED
 SINCE 1926**



United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
 Website: www.penriteoil.com, Email: penrite@penriteoil.com