

# TRACTOR TRANSMISSION AND HYDRAULIC OIL

**Premium Mineral Hydraulic Fluid** 

Issue: November 2013

| Product Code: | Pack Size: | Cartan Oty  |
|---------------|------------|-------------|
| Froduct Code. | Pack Size. | Carton Qty: |
| TTH010        | 10 Litre   | 1           |
| TTH020        | 20 Litre   | 1           |
| TTH205        | 205 Litre  | 1           |
| TTH1000LTR    | 1000 Litre | 1           |



Matural

# **Description**

**Tractor Transmission and Hydraulic Oil** is a multipurpose, 10W-30 / 75W-80 UTTO (Universal Tractor & Transmission Oil) tractor transmission & hydraulic fluid manufactured using highly refined base oils and the latest technology additive package.

### **Application**

**Tractor Transmission and Hydraulic Oil** is designed for use in a wide range of transmissions, hydraulics, PTOs, hydraulic bearings and some final drives of farm tractors and construction equipment, especially those utilising wet brake systems. Can be used as a hydraulic oil where ISO 68 grades are specified.

**Tractor Transmission and Hydraulic Oil** meets the requirements of Case Hytrans Plus, JD 20C/D and API GL-4 as well as many other specifications. It is also suitable for use in the power steering systems of post EF Ford Falcon and its derivatives where a M2C134-D fluid is specified.

**Tractor Transmission and Hydraulic Oil** contains anti wear agents that provide wear protection as well as corrosion protection. It also quietens wet brake chatter without affecting braking performance.

#### Customer Benefits

- Reduces inventory holding as one oil can be used for most applications, also lessening the chance of mis-application.
- Minimises squawk and chatter from wet brake systems.
- Effective anti-wear additives provide wear protection in hydraulic systems.
- Protects against rust and corrosion.
- Long service through good thermal stability.
- Latest technology for maximum protection.

## **Typical Data**

Colour

| Coloui                               | inaturai      |
|--------------------------------------|---------------|
| Density at 15°C                      | 0.873         |
| SAE Grade                            | 10W-30/75W-80 |
| Viscosity, Kinematic, cSt            |               |
| at 40°C                              | 62            |
| at 100°C                             | 10.4          |
| Viscosity Index                      | 157           |
| Zinc, mass %                         | 0.139         |
| Cold Cranking Viscosity, cP at -20°C | 3079          |
| Viscosity, Brookfield, cSt at-18°C   | 2,800         |
| Viscosity, Brookfield, cSt at-35°C   | 30,000        |
| FZG Pass Stage                       | 1             |





See Next page for TTH Industry Active and Obsolete Specifications -

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South Victoria AUSTRALIA 3152, ABN 25 005 001 5 Enquiries: Phone 1300-PENRITE (1300 736 748)
Fax: 1800-PENRITE (1800 736 748)
International: Phone: 61 3 9801 0877,Fax: 61 3 9801 0977
New Zealand Ph: 0800 533 698, Fax: 0508 736 748

PROUDLY AUSTRALIAN FAMILY OWNED SINCE 1926



# API GL-4

AGCO-Allis-Chalmers PowerFluid PF-821 XL, 257541, 246634 Hydr Trans Fluid.

Allison C-4, C-3, C-2.

**Industry Specifications** 

Case New Holland: MAT 3525 / MAT 3526 / MAT 3505 / Case Hydra Trans,

FNHA-2-C-200.00, FNHA-2-C-201.00, NH410 B

Caterpillar: TO-2 / Caterpillar MTO Fluid

Clark TA12 / TA18 / HR500 / HR600

**Denison** (Pump Only) HF0 / HF1 / HF2 **Deutz:** Hyd Trans Fluid, Deutz-Allis 25743

Eaton Vickers (Mobile hydraulic systems - Brochure 694 procedure ATS-373 with 35VQ25 pump)

Ford: M2CA thu C, ESN-M2C134-A/B/C/D, ESN-M2C77-A, ESN-M2C86A/B/C, ESN-M2C41-B, ESN-M2C43, ESN-M2C48-B/C, ESN-M2C53-A/B, ESN-M2C142-A, ESN-M2C143, ESN-M2C92A, ESN-M2C159A/B/C.

Fiat-Hesston AF-87

Sperry Vickers / Eaton I286-S & M2950-S

International Harvester IHC B-5, B-6 Hy-Tran

International Farmall JIC-143 thru 145, JIC 185

**JI Case** MS-1216, MS-1230, MS-1317, MS-143, 144, 145 (TCH Fluid), MS-185 (TFD Fluid), MS-1204, 1205, 1206 (Powergard PFT) /1207 (HyTran Plus) /1209 (HyTran Ultra or Multi) / 1210

John Deere: J27 (10W-30 or 30), JTD303, J14 (A/B/C), J-20 A/B/C/D Hygard, J-121 A, Quatrol

JCMAS (Japanese Construction Mechanization Association) HK P-041 & P042

Komatsu

Kubota UDT Fluid, M80B, Super UDT, Yanmar

**Massey Ferguson** M-1110, M-1127 A/B, M-1129A Permatran, M-1135 Permatran III, M-1138, M-1139 M-1141, M-1143, M-1145.

Landini Tractor Hydr Fluid

Oliver Type 55, 5J

Minneapolis-Moline / White: Q-1705, 1722, 1766, 1766B (UTHF), 1802.

New Idea Q1802

Sauer Sunstrand / Danfoss Hydro Static Trans Fluid

Renk-Doromat 873 or 874 A/B Bus Automatic Trans Fluid

**Valtractores** 

Versatile: Gear & Hydr Trans Fluid 23M & 24M

Volvo VCE 1273.03 and VME WB101

 $\textbf{ZF Transmissions:} \ \mathsf{TE\text{-}ML\text{-}03E} \ \& \ \mathsf{TE\text{-}ML\text{-}05F}, \ \mathsf{TE\text{-}ML\text{-}06K}$ 

Steiger Hydr Trans Fluid, Steiger SEMS 17001

Yanmar

White Farm/Oliver Q-1826



Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect performance. A MSDS is available on request.



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South Victoria AUSTRALIA 3152, ABN 25 005 001 5 Enquiries: Phone 1300-PENRITE (1300 736 748) Fax: 1800-PENRITE (1800 736 748) International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977 New Zealand Ph: 0800 533 698, Fax: 0508 736 748

PROUDLY AUSTRALIAN \*\*
FAMILY OWNED SINCE 1926