

10 Tenths Racing 10 10W-40

Premium PAO & Ester Synthetic Engine Oil

Issue: June 2013

Product Code	Pack Size	Ctn / Qty
RACING10W40001	1 Litre	6
RACING10W40005	5 Litre	4
RACING10W40020	20 Litre	1
RACING10W40205	205 Litre	1





Product Description

Racing 10 is a premium full synthetic PAO & Ester SAE 10W-40, High Zinc, non friction modified, Shear Free modern engine oil. It contains an anti wear package of HIGH ZINC & BORON (exceeding 2200+ ppm levels) for ultimate engine wear protection.

Racing 10 exceeds the exceeds the requirements of API SN/CF, ACEA A3/B3 and JASO MA as well as many manufacturers specifications.

Application

Racing 10 is for use in high performance modern petrol engines for both on road and in competition applications. It is suitable for use in modern 4, 6 & 8+ cylinder, multi-cam, multi-valve including VVT, naturally aspirated, supercharged and turbocharged engines.

Racing 10 is a Shear Free formulation that eliminates viscosity loss and maintains oil pressure during extreme engine operating conditions ensuring the ultimate in protection for your engine.

Racing 10 is suitable for "normal" on road applications in a wide range of vehicles. It can be used where SAE 10W-30 and SAE 10W-40 grade engine oils are specified. It may also be used in petrol and light duty diesel engines up to 2008 where ACEA A3/B4 is specified.

Racing 10 is suitable for use in four stroke motorcycles with wet clutches.

Vehicle Types

Racing 10 is suitable for use in competition applications and on road in passenger cars, motorcycles and light commercial vehicles.



Fuel types

Racing 10 can be used with Petrol, LPG, E10, E85 (Racing & Competition only), diesel (without DPF), avgas, nitro, methanol & other conventional fuels.



Product Benefits

- Blended using PAO and ESTER base oils for maximum heat resistance and high performance
- **HIGH ZINC** & Boron ant-wear additive package for ultimate wear protection
- SHEAR FREE formulation offers start up protection, maintains oil pressure and eliminates viscosity loss (Unbreakable)
- Latest API SN specification for maximum wear protection, minimum sludge and reduced piston deposits
- **COMPETITION PROVEN** and trusted for performance engines
- Can be used in 4 stroke motor cycles with wet clutches.
- Longer engine life by reducing formation of high temperature engine deposits



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South



Industry Specifications

API SN/CF ACEA A3/B3 JASO MA

Manufacturer Specifications

BMW LL-98 MB 229.1 / 229.3 VW 502.00 / 505.00 Porsche GL

Typical Data

Viscosity, Kinematic, cSt at 40°C 92 at 100°C 14.6 Viscosity Index 167 Viscosity, Cold Cranking, cP @ -25°C 6105 CA content, mass % 0.296 P content, mass % 0.152 B content, mass % 0.063 Mo content, ass % 0.010 Zn content, mass % 0.168 Sulphated Ash content, mass % 1.20 Base Number 9.8

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.



