



10 Tenths Racing 20 20W-60

Premium PAO & Ester Synthetic Engine Oil

Issue: June 2013

Product Code	Pack Size	Ctn / Qty
RACING20W60001	1 Litre	6
RACING20W60005	5 Litre	4
RACING20W60020	20 Litre	1
RACING20W60205	205 Litre	1



PENRITE

Product Description

Racing 20 is a premium full synthetic PAO & Ester SAE 20W-60, High Zinc, non friction modified, **Shear Free** modern engine oil. It contains an anti wear package of **HIGH ZINC & BORON** (exceeding 2200+ ppm levels) for ultimate engine wear protection.

Racing 20 exceeds the requirements of API SN/CF, ACEA A3/B3 and JASO MA as well as many manufacturers specifications.

Application

Racing 20 is for use in high performance modern petrol engines for both on road and in competition applications. It is suitable for use in modern 4, 6 & 8+ cylinder, multi-cam, multi-valve including VVT, naturally aspirated, supercharged and turbocharged engines.

Racing 20 is a **Shear Free** formulation that eliminates viscosity loss and maintains oil pressure during extreme engine operating conditions ensuring the ultimate in protection for your engine.

Racing is suitable for "normal" on road applications in a wide range of vehicles. It can be used where SAE 20W-500 and 25W-60 engine oils are specified. It may also be used in light duty petrol and diesel engines up to 2008 where ACEA A3/B4 is specified.

Racing 20 is suitable for use in four stroke motorcycles with wet clutches.

Vehicle Types

Racing 20 is suitable for use in competition applications and on road in passenger cars, motorcycles and light commercial vehicles.

Fuel types

Racing 20 can be used with Petrol, LPG, E10, E85 (Racing & Competition only), diesel (without DPF), avgas, nitro, methanol & other conventional fuels.

Product Benefits

- Blended using **PAO** and **ESTER** base oils for maximum heat resistance and high performance
- **HIGH ZINC** & Boron ant-wear additive package for ultimate wear protection
- **SHEAR FREE** formulation offers **start up** protection, **maintains oil pressure** and **eliminates viscosity loss** (Unbreakable)
- Latest **API SN** specification for maximum wear protection, minimum sludge and reduced piston deposits
- **COMPETITION PROVEN** and trusted for performance engines
- Can be used in 4 stroke motor cycles with wet clutches.
- Longer engine life by reducing formation of high temperature engine deposits



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
 Victoria AUSTRALIA 3152, ABN 25 005 001 525
 Enquiries: Phone 1300-PENRITE (1300 736 748)
 Fax: 1800-PENRITE (1800 736 748)
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748
 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
 Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
 FAMILY OWNED
 SINCE 1926**





Industry Specifications

API SN/CF
ACEA A3/B3
JASO MA

Manufacturer Specifications

BMW LL-98
MB 229.1

Typical Data

Viscosity, Kinematic, cSt	
at 40°C	180
at 100°C	23.9
Viscosity Index	162
Viscosity, Cold Cranking, cP @ -15°C	6323
CA content, mass %	0.296
P content, mass %	0.152
B content, mass %	0.063
Zn content, mass %	0.168
Sulphated Ash content, mass %	1.30
Base Number	9.8

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.

PENRITE



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
Victoria AUSTRALIA 3152, ABN 25 005 001 525
Enquiries: Phone 1300-PENRITE (1300 736 748)
Fax: 1800-PENRITE (1800 736 748)
International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
New Zealand Ph: 0800 533 698, Fax: 0508 736 748
United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
FAMILY OWNED
SINCE 1926**

