

TRACTOR TRANSMISSION AND HYDRAULIC OIL

Premium Mineral Hydraulic Fluid

Issue: November 2013

Product Code:	Pack Size:	Carton Qty:
TTH010	10 Litre	1
TTH020	20 Litre	1
TTH205	205 Litre	1
TTH1000LTR	1000 Litre	1



Natural

Description

Tractor Transmission and Hydraulic Oil is a multipurpose, 10W-30 / 75W-80 UTTO (Universal Tractor & Transmission Oil) tractor transmission & hydraulic fluid manufactured using highly refined base oils and the latest technology additive package.

Application

Tractor Transmission and Hydraulic Oil is designed for use in a wide range of transmissions, hydraulics, PTOs, hydraulic bearings and some final drives of farm tractors and construction equipment, especially those utilising wet brake systems. Can be used as a hydraulic oil where ISO 68 grades are specified.

Tractor Transmission and Hydraulic Oil meets the requirements of Case Hytrans Plus, JD 20C/D and API GL-4 as well as many other specifications. It is also suitable for use in the power steering systems of post EF Ford Falcon and its derivatives where a M2C134-D fluid is specified.

Tractor Transmission and Hydraulic Oil contains anti wear agents that provide wear protection as well as corrosion protection. It also quietens wet brake chatter without affecting braking performance.

Customer Benefits

- Reduces inventory holding as one oil can be used for most applications, also lessening the chance of mis-application.
- Minimises squawk and chatter from wet brake systems.
- Effective anti-wear additives provide wear protection in hydraulic systems.
- Protects against rust and corrosion.
- Long service through good thermal stability.
- Latest technology for maximum protection.

Typical Data

Colour

Density at 15°C	0.873
SAE Grade	10W-30/75W-80
Viscosity, Kinematic, cSt	
at 40°C	62
at 100°C	10.4
Viscosity Index	157
Zinc, mass %	0.139
Cold Cranking Viscosity, cP at -20°C	3079
Viscosity, Brookfield, cSt at-18°C	2,800
Viscosity, Brookfield, cSt at-35°C	30,000
FZG Pass Stage	1





See Next page for TTH Industry Active and Obsolete Specifications -

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South Victoria AUSTRALIA 3152, ABN 25 005 001 5 Enquiries: Phone 1300-PENRITE (1300 736 748)

Fax: 1800-PENRITE (1800 736 748)

International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977

New Zealand Ph: 0800 533 698, Fax: 0508 736 748





Industry Specifications

API GL-4

AGCO-Allis-Chalmers PowerFluid PF-821 XL, 257541, 246634 Hydr Trans Fluid.

Allison C-4, C-3, C-2.

Case New Holland: MAT 3525 / MAT 3526 / MAT 3505 / Case Hydra Trans,

FNHA-2-C-200.00, FNHA-2-C-201.00, NH410 B

Caterpillar: TO-2 / Caterpillar MTO Fluid

Clark TA12 / TA18 / HR500 / HR600

Denison (Pump Only) HF0 / HF1 / HF2

Deutz: Hyd Trans Fluid, Deutz-Allis 25743

Eaton Vickers (Mobile hydraulic systems - Brochure 694 procedure ATS-373 with 35VQ25 pump)

Ford: M2CA thu C, ESN-M2C134-A/B/C/D, ESN-M2C77-A, ESN-M2C86A/B/C, ESN-M2C41-B, ESN-M2C43, ESN-M2C48-B/C, ESN-M2C53-A/B, ESN-M2C142-A, ESN-M2C143, ESN-M2C92A,

ESN-M2C159A/B/C. Fiat-Hesston AF-87

Sperry Vickers / Eaton I286-S & M2950-S

International Harvester IHC B-5, B-6 Hy-Tran

International Farmall JIC-143 thru 145, JIC 185

JI Case MS-1216, MS-1230, MS-1317, MS-143, 144, 145 (TCH Fluid), MS-185 (TFD Fluid), MS-1204, 1205, 1206 (Powergard PFT) /1207 (HyTran Plus) /1209 (HyTran Ultra or Multi) / 1210

John Deere: J27 (10W-30 or 30), JTD303, J14 (A/B/C), J-20 A/B/C/D Hygard, J-121 A, Quatrol

JCMAS (Japanese Construction Mechanization Association) HK P-041 & P042

Komatsu

Kubota UDT Fluid, M80B, Super UDT, Yanmar

Massey Ferguson M-1110, M-1127 A/B, M-1129A Permatran, M-1135 Permatran III, M-1138, M-1139 M-1141, M-1143, M-1145.

Landini Tractor Hydr Fluid

Oliver Type 55, 5J

Minneapolis-Moline / White: Q-1705, 1722, 1766, 1766B (UTHF), 1802.

New Idea Q1802

Sauer Sunstrand / Danfoss Hydro Static Trans Fluid

Renk-Doromat 873 or 874 A/B Bus Automatic Trans Fluid

Valtractores

Versatile: Gear & Hydr Trans Fluid 23M & 24M

Volvo VCE 1273.03 and VME WB101

ZF Transmissions: TE-ML-03E & TE-ML-05F, TE-ML-06K

Steiger Hydr Trans Fluid, Steiger SEMS 17001

Yanmar

White Farm/Oliver Q-1826



Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect performance. A MSDS is available on request.



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South Victoria AUSTRALIA 3152, ABN 25 005 001 5 Enquiries: Phone 1300-PENRITE (1300 736 748) Fax: 1800-PENRITE (1800 736 748) International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977 New Zealand Ph: 0800 533 698, Fax: 0508 736 748

PROUDLY AUSTRALIAN FAMILY OWNED SINCE 1926