

10 Tenths Premium 0 0W-50

Premium 100% PAO & Ester Full Synthetic Engine Oil Issue: September 2013

| Product Code | Pack Size | Ctn / Qty |
|--------------|-----------|-----------|
| FS0W50001 | 1 Litre | 6 |
| FS0W50005 | 5 Litre | 4 |
| FS0W50020 | 20 Litre | 1 |
| FS0W50205 | 205 Litre | 1 |



Product Description

Premium 0 is a premium 100% PAO & Ester full synthetic SAE 0W-50, non friction modified, modern engine oil. It contains a **DOUBLE LAYER** of engine wear protection with ***FULL ZINC +** (exceeding 2200+ ppm levels) and Penrite's advanced **EXTRA TEN** technology.

Premium 0 exceeds the exceeds the requirements of API SN/CF, ACEA A3/B3 as well as many other manufacturers specifications.

Application

Premium 0 is for use in high performance modern engines for both on road and in competition applications. It is suitable for use in modern 4, 6 & 8+ cylinder, multi cam, multi-valve including VVT, naturally aspirated, supercharged & turbocharged engines, including light duty diesel engines.

Premium 0 is suitable for normal on road use in a wide range of vehicles. It can be used where SAE 0W-40 & SAE 5W-40 grade engine oils are specified. It may also be used in light duty petrol and diesel engines up to 2008 where ACEA A3/B4 is specified.

Premium 0 is suitable for use in four stroke motorcycles with wet clutches.

Vehicle Types

Premium 0 is suitable for use in passenger car, light commercial, competition vehicles and motor cycles.

Fuel types

Premium 0 can be used with Petrol, LPG, E10, E85 (Racing & Competition only), diesel (Without DPF), avgas, nitro, methanol & other conventional fuels.

Product Benefits

- ENTERIAL AURILATION
- Blended using 100% PAO (Poly Alpha Olefin Group IV) and ESTER (Group V) full synthetic base oils for maximum heat resistance and high performance
- *FULL ZINC + anti-wear additive package for ultimate engine wear protection
- **EXTRA TEN** which offers the same engine wear protection at start up but with an extra layer of protection under all driving conditions compared to 0W-40 & 5W-40 engine oils.
- LATEST oil specification technology exceeding petrol API SN for maximum wear protection, minimum sludge formation & reduced piston deposits
- Competition proven and trusted for performance engines
- Longer engine life by reducing formation of high temperature engine deposits
- Reduced oil consumption due to use of highly specialised, ultra-pure, low volatility synthetic base oils
- Non-friction modified so can be used in motorcycles with wet clutches
- Very fast flow at start-up combined with full-bodied high temperature protection

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South Victoria AUSTRALIA 3152, ABN 25 005 001 525 Enquiries: Phone 1300-PENRITE (1300 736 748) Fax: 1800-PENRITE (1800 736 748) International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977 New Zealand Ph: 0800 533 698, Fax: 0508 736 748 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234 Website: www.penriteoil.com, Email: penrite@penriteoil.com

PROUDLY AUSTRALIAN FAMILY OWNED SINCE 1926



Industry Specifications

API SN/CF ACEA A3/B3

Manufacturer Specifications

BMW LL-98 MB 229.1 / 229.3 VW 502.00 / 505.00 Porsche GL

Typical Data

| Viscosity, Kinematic, cSt | |
|--------------------------------------|-------|
| at 40°C | 108 |
| at 100°C | 18.7 |
| Viscosity Index | 194 |
| Viscosity, Cold Cranking, cP @ -35°C | 5770 |
| Ca content, mass % | 0.299 |
| B content, mass % | 0.064 |
| Zn content, mass % | 0.169 |
| Base Number | 9.9 |

*Full Zinc + = Zinc level + Boron level combined as a total anti-wear package

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.





 PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South

 Victoria AUSTRALIA 3152, ABN 25 005 001 525

 Enquiries: Phone 1300-PENRITE (1300 736 748)

 Fax: 1800-PENRITE (1800 736 748)

 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977

 New Zealand Ph: 0800 533 698, Fax: 0508 736 748

 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234

 Website: www.penriteoil.com, Email: penrite@penriteoil.com

PROUDLY AUSTRALIAN FAMILY OWNED SINCE 1926