

PRO 5 & PRO 10

Codes: PRO05020, PRO05205, PRO10020, PRO10205

Issue: Aug 2012

Pro 5 and **Pro 10** are premium quality, **semi-synthetic** engine oils developed for use in modern petrol and LPG engines by professional workshop and vehicle service centres. Pro Engine Oils are blended with the latest technology additives along with 100% pure hydrocracked base stocks.

APPLICATION

Pro 5 is recommended where the manufacturer specifies a 5W-20, 5W-30 or 7.5W-30 engine oil. Has General Motors dexos1tm licence so can be utilised whilst the vehicle is within the GM warranty period.

Pro 10 is recommended where the manufacturer specifies a 7.5W-30, or 10W-30 engine oil. Ideal for Ford AU/BF/FG series and Holden VT-II/VX/VY/VZ/VE series vehicles.

Note: Pro 5 and Pro 10 are not recommended for use in newer Mazda rotary engines. Use Everyday 5W-30 or 10W-30 as an alternative.

Pro 5 and Pro 10 are not for use in diesel vehicles.

Customer Benefits

- Catalytic converter compatible.
- Minimises sludge formation
- Maximises wear protection
- · Reduces piston deposits

Industry Specifications

Pro 5 API SN Resource Conserving, ILSAC GF-5, Ford M2C 910A, GM dexos1tm

Pro 10 API SN Resource Conserving, ILSAC GF-5, Ford M2C 910A

Typical Data

PR0 5	PRO 10
5W-30	10W-30
0.851	0.866
63	60
11.0	9.8
169	148
	3,966
5,020	
0.085	0.082
0.93	0.95
7.2	8.3
	0.851 63 11.0 169 5,020 0.085 0.93





Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.





