



PENRITE

# 5 YEAR EXTENDED DRAIN ANTI FREEZE ANTI BOIL

## CONCENTRATE:

5YRAFAB001, 5YRAFAB005, 5YRAFAB010, 5YRAFAB020, 5YRAFAB060 5YRAFAB205

## 50% READY TO USE PREMIX:

5YRAFABPMX001, 5YRAFABPMX005, 5YRAFABPMX010, 5YRAFABPMX020, 5YRAFABPMX205

Issue: September 2012

A fully organic, OEM Approved, European style, ethylene glycol based coolant, concentrate and premix.

### Application

Suitable for the cooling systems of petrol, LPG, light and heavy duty diesel and industrial engines where anti-freeze and/or anti-boil properties are required.

It has particular suitability for cars and heavy duty diesel engines of European origin but may be used in all types of vehicles that use red, magenta or orange coloured initial fill coolants. It is also ideal for motorcycles.

Penrite 5YR Extended Drain Anti Freeze Anti Boil Concentrate should be used at a concentration of between 33% and 50%.

Dose	Freezing Point	Boiling Point
33%	-18°C	104°C
50%	-38°C	109°C

### Customer Benefits

- 5 year or 250,000 km (whichever comes first) drain intervals if used and maintained at 50%.
- Compatible with plastics, rubbers and seals.
- Protects all internal surfaces from corrosion, including aluminium.
- Phosphate free formulation allows use with hard water.
- Silicate, borate, nitrite and amine free

### Industry Specifications:

AS2108-2004 Type A	ASTM D3306	BS 6580	JIS K2234 (Japan)
JASO M325 (Japan)	KSM 2142 (Korea)	SAE J1034	UNE 26.361.88

### OEM Approvals:

Audi/Bentley/Lamborghini/SEAT/Skoda/VW TL 774-D/F (G12,G12+)	MAN 324 SNF
MTU MTL 5048	Porsche, 1996 - 2010
	Mini Cooper D, 2007 Onwards

### Also meets the requirements and specifications of the following:

Alfa Romeo	Audi TL 774-D/F	Bentley TL 774-D/F
Chevrolet	Cummins 85T8-2	Daihatsu
Deutz AG 0199-99-1115/2091	Ferrari	Fiat 955523/NC 956-16
Ford ESE M97-B44D	German Army TL6850-0038/1	GM 6277M/1825M/1899M
Holden GM6277M	Honda	Hyundai
Jaguar M97-B44D	JI Case JIC 501	Jeep
Jenbacher TA 1000-0201	John Deere	KIA
Lamborghini TL 774-D/F	Lancia	Land Rover
Lexus	Lotus	Mazda
Mercedes MB 326.3 (Premix Only)	MG Rover	MINI (Diesel)
Mitsubishi ES-X64217	Nissan NES M5059	Opel B 040 1065
Porsche	Renault 41-01-001Q Type D	SAAB GM6277M
SEAT TL 774-D/F	Skoda TL 774-D/F	Subaru
Suzuki	Toyota Long Life TSK2601G	Vauxhall B 040 1065
VW TL 774-D/F	Volvo	

### Heavy Duty Trucks:

Daewoo	DAF-Leyland	Mitsubishi Fuso	MTU
Nissan (UD)	Renault	Scania T1.02-98 0813	Volvo

To ensure you use the correct coolant in your vehicle, refer to the Penrite Recommendation Guide located at [www.penriteoil.com](http://www.penriteoil.com) or refer to your owner's handbook.

### Typical Data

Colour	Magenta
Density at 15°C, kg/L	1.124
Glycol Content (Concentrate), g/L	1075
Glycol Content (Premix 50%), g/L	537



**PENRITE OIL COMPANY PTY LTD**, 88 Lewis Road, Wantirna South  
 Victoria AUSTRALIA 3152, ABN 25 005 001 525  
 Enquiries: Phone 1300-PENRITE (1300 736 748)  
 Fax: 1800-PENRITE (1800 736 748)  
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977  
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748  
 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234  
 Website: [www.penriteoil.com](http://www.penriteoil.com), Email: [penrite@penriteoil.com](mailto:penrite@penriteoil.com)

**PROUDLY AUSTRALIAN  
 FAMILY OWNED  
 SINCE 1926**

