



# COPPER EZE

Product Code:	Pack Size:	Carton Qty:
CEZE00005	50 gram	12
CEZE0005	500 gram	12

**Issue: May 2013**

A bentone based anti-seize grease containing micro-size copper, zinc oxide and additional synthetic base oil that will resist temperatures of up to 1093°C.

### Application

Used to coat flanges, threads, nuts, bolts etc prior to assembly, to enable easy disassembly. Is also ideal for exhaust manifold studs, turbocharger connections, spark plug threads, drum and disc brake assemblies.

It may be used in all types of industries including in corrosive marine and mining environments, petroleum (exploration, refining) industry.

It may be used at all temperatures from sub-zero to 1093°C.

### Customer Benefits

- Protects against corrosion in severe environments.
- Reduces friction and wear
- Synthetic lubricant forms a tough plating in metal pores to prevent galling
- Low toxicity
- Protects against seizing
- Resists high temperatures
- Reduces torque during assembly

### CAUTION

Should not be used on internal components of engines, transmissions or brake systems.

### Industry Specifications

NLGI 1.5

### Typical Data

Appearance  
 Soap Type  
 Dropping Point, °C  
 Solidification Point, °C

Copper  
 Bentone Clay  
 non-melt  
 -18

# PENRITE



Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. A MSDS is available on request.

**PENRITE OIL COMPANY PTY LTD**, 88 Lewis Road, Wantirna South  
 Victoria AUSTRALIA 3152, ABN 25 005 001 525  
 Enquiries: Phone 1300-PENRITE (1300 736 7483)  
 Fax: 1800-PENRITE (1800 736 7483)  
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977  
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748

**PROUDLY AUSTRALIAN  
 FAMILY OWNED  
 SINCE 1926**



**United Kingdom and EU** Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234  
 Website: [www.penriteoil.com](http://www.penriteoil.com), Email: [penrite@penriteoil.com](mailto:penrite@penriteoil.com)