



# EVERYDAY FULL SYNTHETIC 10W-40

## Full Synthetic Engine Oil

Issue: September 2013



Product Code	Pack Size	Ctn / Qty
EDS10006	6 Litre	3

### Product Description

**Everyday Full Synthetic 10W-40** is a premium, full synthetic, SAE 10W-40 engine oil. Contains a **DOUBLE LAYER** of engine wear protection with **FULL ZINC** and Penrite's advanced **EXTRA TEN** technology. It uses a combination of the latest additive technology and a low shear rate viscosity modifier, to ensure additional protection against wear, corrosion, oil oxidation, piston deposits and sludge under all conditions.

### Application

**Everyday Full Synthetic 10W-40** is designed for use in modern 4, 6 & 8+ cylinder multi-cam, multi-valve (including VVT), naturally aspirated, supercharged & turbocharged engines.

**Everyday Fully Synthetic 10W-40** exceeds the requirements of API SN/CF and the European Standards ACEA A3/B4, as well as many manufacturers' specifications. It is designed for use where SAE10W-30, SAE 10W-40 and SAE 15W-40 grade oils are recommended in the owners handbook. It may be used in light duty diesel engines where ACEA A3/B3 or A3/B4 is specified by the manufacturer.

**Everyday Fully Synthetic 10W-40** is suitable for use in passenger cars, 4WD's, motorcycles & light commercial vehicles. It is suitable for use in four stroke motorcycles with wet clutch.

**Everyday Fully Synthetic 10W-40** is compatible with Petrol/LPG (Dual Fuel), E10, Diesel and most other other conventional fuels. If using with E85 fuel, Penrite recommend more frequent oil change periods.

### Customer Benefits

- **EXTRA TEN** technology offers the same engine wear protection at start up, but offers an extra layer of protection under all driving conditions compared to SAE10W-30 engine oils
- **FULL ZINC** anti-wear additive package for ultimate engine wear protection
- **LATEST** oil specification technology exceeding **API SN** and **ACEA A3/B4** for maximum wear protection, minimum sludge formation & reduced piston deposits
- Reduces oil consumption and maintains oil pressure
- Longer engine life by reducing formation of high temperature engine deposits
- Competition proven and trusted protection for performance engines

### Industry Specifications

API SN/CF  
BMW LL-01

ACEA A3/B4 (Europe)  
MB 229.3/229.5

JASO MA

### Typical Data

Density at 15°C, kg/L	0.865
Viscosity, Kinematic, cSt	
at 40°C	97
at 100°C	15.1
Viscosity Index	165
Viscosity, Cold Cranking @ -25°C	5,049
Zinc, mass %	0.124
Sulphated Ash, mass %	1.17
Base Number	9.5

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.



**PENRITE OIL COMPANY PTY LTD**, 88 Lewis Road, Wantirna South  
Victoria AUSTRALIA 3152, ABN 25 005 001 525  
Enquiries: Phone 1300-PENRITE (1300 736 748)  
Fax: 1800-PENRITE (1800 736 748)  
International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977  
New Zealand Ph: 0800 533 698, Fax: 0508 736 748  
United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234  
Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN  
FAMILY OWNED  
SINCE 1926**

