

INDUS PRO HYDRAULIC OILS

Premium Mineral Oil Issue: May 2015

PRODUCT CODE	PACK SIZE	PRODUCT CODE	PACK SIZE
PROHYD10205	205 Litre	PROHYD46005	5 Litre
PROHYD22205	205 Litre	PROHYD46020	20 Litre
PROHYD32005	5 Litre	PROHYD46205	205 Litre
PROHYD32020	20 Litre	PROHYD461000LTR	1000 Litre
PROHYD32205	205 Litre	HYD68001	1 Litre
PROHYD68005	5 Litre	PROHYD68020	20 Litre
PROHYD68205	205 Litre	PROHYD681000LTR	1000 Litre



Description

Indus Pro Hydraulic Oils are a premium mineral range of high quality, low and zinc free (ISO 10 & 22) hydraulic oils made from selected base stocks and advanced anti-wear additive packages. They are available in ISO 10, 22, 32, 46 & 68 grades to satisfy the requirements of stationary, mobile and industrial machines.

Application

Indus Pro Hydraulic Oils are recommended for use in all types of hydraulic systems using vane, piston or gear pumps, airline lubricators, vacuum pumps, lightly loaded gear sets and bearings (such as headstocks & windmill gears) as well as hydraulic hoists and jacks.

Indus Pro Hydraulic Oils can be used with silver components due to their suitable formulation and are safe for all hydraulic hoses & seal types. They also provide outstanding protection against wear and corrosion.

Product Benefits

- Formulated to combat rust, oxidation, wear and foaming.
- Reduces sludge formation.
- Compatible with silver components.
- Provides good water separation.

Industry Specifications

Denison HF0, HF1, HF2 US Steel 126, 127

Vickers I-286-S, M-2950-S DIN 51524 Part 2 (HLP Type) Cincinnati Milacron P-68 (32), P-69 (68), P-70 (46) (HM)

PROUDLY AUSTRALIAN

FAMILY OWNED

SINCE 1926

Typical Data

51	PROHYD10	PROHYD22	PROHYD32	PROHYD46	PROHYD68
ISO Grade	10	22	32	46	68
Viscosity, Kinematic, cSt					
at 40°C	11	19.2	30.2	44.6	72.1
at 100°C	2.8	4.3	5.1	6.7	9.0
Viscosity Index	116	131	94	103	98
Zinc, mass %	NIL	NIL	0.032	0.032	0.032



Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South Victoria AUSTRALIA 3152, ABN 25 005 001 525 Enquiries: Phone 1300-PENRITE (1300 736 748) Fax: 1800-PENRITE (1800 736 748) International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977 New Zealand Ph: 0800 533 698, Fax: 0508 736 748

United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234 Website: www.penriteoil.com, Email: penrite@penriteoil.com