

# **AUTO TRANS STOP LEAK**

### **Automatic Transmission Leak Sealer**

Issued: December 2015

| Product Code | Pack Size | Ctn / Qty |
|--------------|-----------|-----------|
| ADTSL375     | 375ml     | 6         |



## **Description**

**Auto Transmission Stop Leak** has been specifically formulated to control leaks in automatic transmission systems due to deteriorating or worn seals and gaskets.

## **Application:**

**Auto Transmission Stop Leak** has been designed for use in conventional automatic transmissions units. It is suitable for cars, 4WDs, and light commercial vehicles.

Auto Transmission Stop Leak is suitable for use with vehicles that use the following Penrite automatic

transmission fluids -

Penrite Multi-Vehicle DX-III

Penrite Multi-Vehicle DX-VI

Penrite Multi-Vehicle MHP

Penrite Multi-Vehicle FS Penrite ATF 33 Type

Penrite ATF Top Up

Penrite Classic ATF

#### Note:

Cannot be used in CVT, DCT or DSG type transmissions.

### For best results:

- One 375ml bottle treats up to 10 Litres of transmission fluid.
- Add one bottle (375ml) through automatic transmission filling point.

### Note:

If leaks are still evident after use, replacement or repair of these parts may be required.

### **Product Benefits**

- Revitalises worn seals and gaskets
- Reduces leaks
- Contains additives to maintain transmission performance
- Compatible with Mineral and Synthetic ATF's
- · Extends component life
- Compatible with automatic transmission sensors
- Reduces noise and wear





 Colour
 Amber

 Density at 15°C, kg/L
 0.863

 Viscosity, Kinematic, cSt
 86

 40°C
 86

 100°C
 16.7

 Viscosity Index
 211



Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect performance. A MSDS is available on request.

