



COPPER EZE

Codes: CEZE00005, CEZE0005
Pack Sizes: 50 Gram, 500 Gram
Issue: December 2012

A bentone based anti-seize grease containing micro-size copper, zinc oxide and additional synthetic base oil that will resist temperatures of up to 1093°C.

Application

Used to coat flanges, threads, nuts, bolts etc prior to assembly, to enable easy disassembly. Is also ideal for exhaust manifold studs, turbocharger connections, spark plug threads, drum and disc brake assemblies.

It may be used in all types of industries including in corrosive marine and mining environments, petroleum (exploration, refining) industry.

It may be used at all temperatures from sub-zero to 1093°C.

Customer Benefits

- Protects against corrosion in severe environments.
- Reduces friction and wear
- Synthetic lubricant forms a tough plating in metal pores to prevent galling
- Low toxicity
- Protects against seizing
- Resists high temperatures
- Reduces torque during assembly

CAUTION

Should not be used on internal components of engines, transmissions or brake systems.

Industry Specifications

NLGI 1.5

Typical Data

Appearance

Soap Type

Dropping Point, °C

Solidification Point, °C

Copper
Bentone Clay
non-melt
-18

PENRITE



Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. A MSDS is available on request.

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
Victoria AUSTRALIA 3152, ABN 25 005 001 525
Enquiries: Phone 1300-PENRITE (1300 736 7483)
Fax: 1800-PENRITE (1800 736 7483)
International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
New Zealand Ph: 0800 533 698, Fax: 0508 736 748

United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
FAMILY OWNED
SINCE 1926**

