GRAPHITE GREASE

Calcium Base Grease

Issue: May 2016

PRODUCT CODE	PACK SIZE	CTN / QTY
GRGR0005	500gm	6

Description

Penrite Graphite Grease is a grey/black coloured, NLGI 3, graphite impregnated calcium based grease

Application

Penrite Graphite Grease is designed for the lubrication of spring leaves, handbrake cables, flexible drives and exposed chains.

Penrite Graphite Grease is suitable for use in slow speed plain bearings and slides where a heavy grease with solid lubricants is required.

Penrite Graphite Grease can also be used in industrial, mining and construction equipment including bulldozers, scrapers, loading shovels and dump trucks where graphite grease is recommended and high temperature capability is not required.

Penrite Graphite Grease can be used in plain bearing locks, latches and fasteners, cables and springs and even as a fifth wheel lubricant.

Note: Should not be used in wheel bearings or where temperatures are likely to exceed 60&#176C.

Product Benefits

- Good resistance to water washout
- Long service life
- Protects against wear, rust and corrosion

Industry Specifications

NLGI 3

Typical Data

Appearance	Grey/Black
Soap Type	Calcium
NLGI Grade	3
Drop Point, °C	80
Graphite Content, %	15

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
Victoria AUSTRALIA 3152, ABN 25 005 001 525
Enquiries: Phone 1300-PENRITE (1300 736 748)
Fax: 1800-PENRITE (1800 736 748)
International: Phone: 61 3 9801 0877,Fax: 61 3 9801 0977
New Zealand Ph: 0800 533 698, Fax: 0508 736 748

PROUDLY AUSTRALIAN
FAMILY OWNED
SINCE 1926

United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
Website: www.penriteoil.com, Email: penrite@penriteoil.com