HD OIL

Codes: HD005
Issue: November 2011

Description

SAE 50-70 non-friction modified four stroke motorcycle engine oil for older large capacity engines. It is made from a unique combination of additives and viscosity modifiers that have been shown to control deposit formation in older motorcycles.

Application

Primarily recommended for use in classic motorcycles where SAE 50 monograde oils were specified. In particular, it may be used in pre-Evolution (1984) engined Harley Davidson motor cycles and other large V-Twin bikes such as Indian and Henderson. HD Oil is also ideal oil for Classic British motorcycles including single cylinder 350 to 500cc low revving engines and 500 to 650cc Parallel twins.

Customer Benefits

- Maintains oil pressure and reduces oil consumption.
- Provides good valve train wear protection.
- Maintains engine cleanliness through unique detergent and viscosity modifier combination.
- Non-friction modified to maintain clutch effectiveness.

Industry Specifications

API SF

Typical Data

Density at 15°C, kg/L	0.890
Viscosity, Kinematic, cSt	
at 40°C	281
at 100°C	28.8
Viscosity Index	137
Sulphated Ash, mass %	0.98
Base Number	7.4
Zinc, mass %	0.176

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. A MSDS is available on request.

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
Victoria AUSTRALIA 3152, ABN 25 005 001 525
Enquiries: Phone 1300-PENRITE (1300 736 7483
Fax: 1800-PENRITE (1800 736 7483)
International: Phone: 61 3 9801 0877,Fax: 61 3 9801 0977
New Zealand Ph: 0800 533 698, Fax: 0508 736 748
United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
Website: www.penriteoil.com, Email: penrite@penriteoil.com

PROUDLY AUSTRALIAN
FAMILY OWNED
SINCE 1926