



# HPR

## HPR 0

### Full Synthetic 0W-30 Engine Oil

Issue: December 2015

Product Code	Pack Size	Ctn / Qty
HPR00001	1 Litre	6
HPR00005	5 Litre	4
HPR00020	20 Litre	1
HPR00205	205 Litre	1

### Product Description

**HPR 0** is a premium, full synthetic SAE 0W-30 engine oil. Contains a **DOUBLE LAYER** of engine wear protection with **FULL ZINC** and Penrite's advanced **EXTRA TEN** technology. It uses a combination of the latest additive technology and a low shear rate viscosity modifier, to ensure additional protection against wear, corrosion, oxidation, piston deposits and sludge under tough conditions.

**HPR 0** exceeds the requirements of API SL/CF, ACEA A3/B4 as well as many manufacturers' specifications.

### Application

**HPR 0** is designed for use in modern 4, 6 & 8+ cylinder multi-cam, multi-valve (including VVT), naturally aspirated, supercharged & turbocharged engines, including petrol/electric hybrids.

**HPR 0** is suitable for vehicles that specify the use of SAE 0W-30, SAE 5W-20 or 0W-20 low viscosity engine oils as specified in the owner's handbook.

**HPR 0** can be used where the ILSAC GF-3/GF-4, ACEA A1/B1 and A5/B5 fuel economy specifications are specified by the manufacturer.

**HPR 0** is suitable for use in LPG and light duty diesel engines. It is also suitable for use in Hybrid powered petrol/electric vehicles where this viscosity and specification are requested by the manufacturer. It is **NOT** suitable for use in diesels fitted with a DPF (Diesel Particulate Filter) or in four stroke motorcycles.

### Vehicle & Fuel Types

**HPR 0** is suitable for use in passenger cars, 4WD's & light commercial vehicles and is compatible with Unleaded Petrol/LPG (Dual Fuel)/E10 & Diesel and other conventional fuels.

### Product Benefits

- **EXTRA TEN** technology offers the same engine wear protection at start up, but offers an extra layer of protection under all driving conditions compared to SAE 5W-20 & SAE 0W-20 engine oils
- **FULL ZINC** anti-wear additive package for ultimate engine wear protection
- Can be used in both petrol & diesel engines
- Low start-up viscosity allows easy starting in hydraulically actuated injector equipped engines
- Longer engine life by reducing formation of high temperature engine deposits
- Low start-up viscosity provides engine protection and power/fuel economy retention at the most critical time of the engine's run cycle
- Suitable for **HYBRID** petrol/electric vehicles
- Reduces wear by controlling soot deposits in diesel engines



# PENRITE



**PENRITE OIL COMPANY PTY LTD**, 88 Lewis Road, Wantirna South  
 Victoria AUSTRALIA 3152, ABN 25 005 001 525  
 Enquiries: Phone 1300-PENRITE (1300 736 748)  
 Fax: 1800-PENRITE (1800 736 748)  
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977  
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748  
 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234  
 Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN  
 FAMILY OWNED  
 SINCE 1926**





## Industry Specifications

API SL/CF  
ACEA A3/B4

*\* Passes all engine test performance requirements of API SN and SM but although using the same base chemistry, cannot claim API SM or SN due to the full zinc content.*

## Manufacturer Specifications

BMW Longlife-01  
MB 229.3 / 229.5  
GM 4718M  
Ford M2C913-A/913-B

## Typical Data

Density at 15°C, kg/L	0.854
Viscosity, Kinematic, cSt	
at 40°C	64
at 100°C	11.4
Viscosity Index	174
Cold Cranking Viscosity, cP at -35°C	5765
Zinc, mass %	0.105
Phosphorus, mass %	0.096
Sulphated Ash, mass %	1.09
Base Number	10.1

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.

# PENRITE



**PENRITE OIL COMPANY PTY LTD**, 88 Lewis Road, Wantirna South  
Victoria AUSTRALIA 3152, ABN 25 005 001 525  
Enquiries: Phone 1300-PENRITE (1300 736 748)  
Fax: 1800-PENRITE (1800 736 748)  
International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977  
New Zealand Ph: 0800 533 698, Fax: 0508 736 748  
United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234  
Website: [www.penriteoil.com](http://www.penriteoil.com), Email: [penrite@penriteoil.com](mailto:penrite@penriteoil.com)

**PROUDLY AUSTRALIAN  
FAMILY OWNED  
SINCE 1926**

