

# INDUS PRO HYDRAULIC OILS

**Premium Mineral Oil** Issue: October 2015

PRODUCT CODE	RODUCT CODE PACK SIZE		
PROHYD10205	205 Litre	205 Litre 1	
PROHYD22205	205 Litre	1	
PROHYD32005	5 Litre	itre 4	
PROHYD32020	20 Litre	1	
PROHYD32205	205 Litre	1	
PROHYD46005	5 Litre	4	
PROHYD46020	20 Litre	1	
PROHYD46205	205 Litre	1	
PROHYD461000LTR	1000 Litre	1	
HYD68001	1 Litre	6	
PROHYD68005	5 Litre	4	
PROHYD68020	20 Litre	1	
PROHYD68205	205 Litre	1	
PROHYD681000LTR	1000 Litre	1	



#### **Description**

Indus Pro Hydraulic Oils are a premium mineral range of high quality, low and zinc free (ISO 10 & 22) hydraulic oils made from selected base stocks and advanced anti-wear additive packages. They are available in ISO 10, 22, 32, 46 & 68 grades to satisfy the requirements of stationary, mobile and industrial machines.

### Application

Indus Pro Hydraulic Oils are recommended for use in all types of hydraulic systems using vane, piston or gear pumps, airline lubricators, vacuum pumps, lightly loaded gear sets and bearings (such as headstocks & windmill gears) as well as hydraulic hoists and jacks.

Indus Pro Hydraulic Oils can be used with silver components due to their suitable formulation and are safe for all hydraulic hoses & seal types. They also provide outstanding protection against wear and corrosion.

### **Product Benefits**

- Formulated to combat rust, oxidation, wear and foaming.
- Reduces sludge formation.
- Compatible with silver components.
- Provides good water separation.

### Industry Specifications

Denison HF0, HF1, HF2	Vickers I-286-S, M-2950-S	DIN 51524 Part 2 (HLP Type)
US Steel 126, 127	Cincinnati Milacron P-68 (32),	P-69 (68), P-70 (46) (HM)

## **Typical Data**

CAS INTERNATIONAL ISO 9001:2008 REGISTERATION MANUAL CARDING OF		150 9001:2008
--	--	---------------

SGS

N.

	PROHYD10	PROHYD22	PROHYD32	PROHYD46	PROHYD68
ISO Grade	10	22	32	46	68
Viscosity, Kinematic, cSt					
at 40°C	11	19.2	30.2	44.6	72.1
at 100°C	2.8	4.3	5.1	6.7	9.0
Viscosity Index	116	131	94	103	98
Zinc, mass %	NIL	NIL	0.032	0.032	0.032

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South Victoria AUSTRALIA 3152, ABN 25 005 001 525 Enquiries: Phone 1300-PENRITE (1300 736 748) Fax: 1800-PENRITE (1800 736 748) nal: Phone: 61 3 9801 0877,Fax: 61 3 9801 0977 New Zealand Ph: 0800 533 698, Fax: 0508 736 748

### PROUDLY AUSTRALIAN FAMILY OWNED **SINCE 1926**

United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234 Website: www.penriteoil.com, Email: penrite@penriteoil.com