

# **MARINE GEAR OIL 75W-90**

Outboard & Stern Drive Gear Oil Januar May 2015

ISSUE. May 2015						
	Product Code	Pack Size	Ctn / Qty			
	MAR75900005	500 ml	6			
	MAR7590020	20 Litre	1			

# **NEW "BLUE" COLOURED FULL SYNTHETIC**



## **Description**

Marine Gear Oil 75W-90 is a BLUE coloured, FULL SYNTHETIC SAE 75W-90 gear oil formulated to meet the requirements of outboard gear cases and marine stern drive units. It provides outstanding protection from cold start to operating temperatures, making gear selection and engagement smoother and easier.

### Application

Marine Gear Oil 75W-90 is designed to be used in outboard and marine stern drive gear cases where the manufacturer recommends an SAE 75W-90 gear case oil. It can be used where an API GL-5 SAE 80W-90 or SAE 90 is recommended.

Marine Gear Oil 75W-90 is suitable for the following outboards engine as gear case oil:

Chrysler	Condor	Evinrude	Force	Hanimex	Hidea
Honda	Johnson	Mariner	Mercury	Nissan	OMC
Suzuki	Tohatsu	Volvo Penta	Yamaha	& Others	

Note: Exceptions are where a special oil or fluid is called for (particularly jet units), Mariner Electric trolling motors and Mercury Electric Thrusters, both of which must use Penrite ATF DX-III.

Marine Gear Oil 75W-90 is suitable for the following stern drive units:

Chrysler Drive 90, 300	Condor	Cummins
Evinrude-Johnson	Mercruiser	OMC Drives
Yamaha Drives	Volvo Penta	Yanmar Saildrives

Note: Some Chrysler, Volvo Penta and Yanmar units require engine oils. Please check the owner's manual and the Penrite lube guide prior to selection of lubricant.

#### Product Benefits

- Full Synthetic performance and protection.
- Easy gear engagement at low temperatures.
- Longer oil and component life.
- Superior thermal and oxidation stability.
- Outstanding protection at operating temperatures.

## Industry Specifications

API GL-5



### **Typical Data**

- )	
Density at 15 <sup>°</sup> C, kg/L	0.869
Viscosity, Kinematic, cSt	
at 40°C	99
at 100°C	14.9
Viscosity Index	157
Brookfield Viscosity @ -40°C, cP	146,000
Phosphorus, mass %	0.040
Colour	Blue

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South Victoria AUSTRALIA 3152, ABN 25 005 001 525 Enquiries: Phone 1300-PENRITE (1300 736 748) Fax: 1800-PENRITE (1800 736 748) nternational: Phone: 61 3 9801 0877,Fax: 61 3 9801 0977 New Zealand Ph: 0800 533 698, Fax: 0508 736 748 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234 Website: www.penriteoil.com, Email: penrite@penriteoil.com

## PROUDLY AUSTRALIAN FAMILY OWNED **SINCE 1926**