



MC-4 MINERAL 20W-50

Premium Mineral Engine Oil

Issue: March 2017

Product Code	Pack Size	Carton Qty
MC420W50001	1 Litre	6
MC420W50004	4 Litre	4
MC420W50020	20 Litre	1

Product Description

MC-4 MINERAL 20W-50 is a premium, high performance mineral, SAE 20W-50, non friction modified, 4 stroke engine oil. It contains a superior anti wear package of **FULL ZINC** (exceeding 1200+ ppm) for ultimate engine, gearbox & clutch protection.

MC-4 MINERAL 20W-50 meets the requirements of API SG/CF and JASO MA.

Application

MC-4 MINERAL 20W-50 is designed for use in four stroke road & sports bikes, dirt & enduro bikes, ATV's/Quad bikes and scooters. It is also equally suitable for use in transmissions with wet clutch systems where engine & gearbox oils are combined. It has optimum clutch slip prevention in these systems being compliant with JASO MA as well as meeting the performance requirements of JASO MA1 and JASO MA2.

MC-4 MINERAL 20W-50 is designed for use in high performance, 4 stroke motorcycle engines in applications where a premium mineral oil is specified by the manufacturer. It can be used where SAE 20W-50 grade oils are specified by the manufacturer such as in **Buell, Victory & Harley Davidson** and more.

MC-4 MINERAL 20W-50 is also suitable for use in other four stroke engines such as stationary engines & generators or other vehicles that require this grade and specification of engine oil and can be used with petrol, racing & other conventional fuels.

Product Benefits

- **FULL ZINC** anti-wear additive package for ultimate engine wear protection
- **MAXIMUM** power and acceleration
- **FACTORY PROVEN** by competition race teams and trusted protection for performance engines
- **SHEAR STABLE** for long term protection
- Suitable for use with wet clutch systems (JASO MA, JASO MA1 and JASO MA2)
- Longer engine life by reducing formation of high temperature engine deposits

Industry Specifications

API SG/CF

JASO MA

Typical Data

Density at 15°C, kg/L	0.872
Viscosity, Kinematic, cSt	
at 40°C	183
at 100°C	20.8
Viscosity Index	134
Viscosity, Cold Cranking @ -15°C	6841
Zinc, mass %	0.110
P content, mass %	0.100
Sulphated Ash, mass %	0.8
Base Number	5.8

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request. Penrite recommend the right product for the right application. Please consult the Penrite lube guide for the correct oil recommendation.



PENRITE



PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South
 Victoria AUSTRALIA 3152. ABN 25 005 001 525
 Enquiries: Phone 1300-PENRITE (1300 736 7483)
 Fax: 1800-PENRITE (1800 736 7483)
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977
New Zealand Ph: 0800 533 698, Fax: 0508 736 748
United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234
 Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
 FAMILY OWNED
 SINCE 1926**

