

MOLYGREASE EP 3%

Codes: MOLY00045, MOLY0005, MOLY0025, MOLY020, MOLY055, MOLY180

Issue: October 2011

An NLGI No 2 high temperature all-purpose grease manufactured from high quality base oils, a lithium soap and containing molybdenum disulphide (moly) for added protection.

Application

General grease applications in automotive and industrial service.

It is particularly suitable for use where the grease is likely to be exposed to the weather and/or squeezed out. In these applications, a thin film of molybdenum will provide some measure of protection until the component can be re-greased.

Recommended for use on ball joints, king pins and universal joints.

It is also a highly effective industrial grease and may be used in plain bearings, slow speed bearings (not anti-friction), as a chassis grease, general plant lubrication and in agricultural and construction equipment lubrication.

Customer Benefits

- Protects against shock loadings.
- Excellent resistance to water wash out and squeeze out.
- Protects against rust and corrosion.
- Long service life.
- Moly provides lubrication even if base grease is squeezed out.
- Tackiness additive helps grease stay in place, extending regreasing intervals.

Industry Specifications

NLGI 2

Typical Data

Soap Type Lithium Water Washout at 80°C, % 4 Base Oil Viscosity, ISO 220 Drop Point, °C 190 Colour Grey/Black Timken OK Load, kg 18 Four Ball Weld Load, kg 315 **Appearance** Stringy/Tacky Solids Content, %





Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. A MSDS is available on request.

PENRITE OIL COMPANY PTY LTD, 88 Lewis Road, Wantirna South Victoria AUSTRALIA 3152, ABN 25 005 001 525
Enquiries: Phone 1300-PENRITE (1300 736 7483
Fax: 1800-PENRITE (1800 736 7483)
International: Phone: 61 3 9801 0877,Fax: 61 3 9801 0977

PROUDLY AUSTRALIAN FAMILY OWNED SINCE 1926

New Zealand Ph: 0800 533 698, Fax: 0508 736 748