



Product Information

MOLYGREASE EP 3%

Codes: MOLY00045, MOLY0005, MOLY0025, MOLY020, MOLY055, MOLY180

Issue: January 2010

An NLGI No 2 high temperature all purpose grease manufactured from high quality base oils, a lithium soap and containing molybdenum disulphide (moly) for added protection.

APPLICATION

Molygrease EP 3% is suitable for use in most general grease applications in automotive and industrial service.

It is particularly suitable for use where the grease is likely to be exposed to the weather and/or squeezed out. In these applications, a thin film of molybdenum will provide some measure of protection until the component can be re-greased.

Recommended for use on ball joints, king pins and universal joints.

It is also a highly effective industrial grease and may be used in plain bearings, slow speed bearings (not anti-friction), as a chassis grease, general plant lubrication and in agricultural and construction equipment lubrication.

CUSTOMER BENEFITS

- Protects against shock loadings.
- Excellent resistance to water wash out and squeeze out.
- Protects against rust and corrosion.
- Long service life.
- Moly provides lubrication even if base grease is squeezed out.
- Tackiness additive helps grease stay in place, extending regreasing intervals.

SPECIFICATIONS

NLGI 2

Typical Properties

Soap Type	Lithium
Water Washout at 80°C, %	4
Base Oil Viscosity, ISO	220
Drop Point, °C	190
Colour	Grey/Black
Timken OK Load, kg	18
Four Ball Weld Load, kg	315
Appearance	Stringy/Tacky
Solids Content, %	3